

## [MS-DTSX]: Data Transformation Services Package XML File Format

This topic lists the Errata found in the MS-DTSX document since it was last published. Since this topic is updated frequently, we recommend that you subscribe to these RSS or Atom feeds to receive update notifications.



Errata are subject to the same terms as the Open Specifications documentation referenced.

Errata below are for Data Portability Document Version [V8.0 – 2021/02/11](#).

| Errata Published* | Description  |
|-------------------|--|
| 2021/09/21        | <p>In sections 2.4, ExecutableTypePackage, 2.6.2.1, ExecutableType Instance for Sequence, 2.6.2.2, ExecutableType Instance for ForEachLoop, and 2.6.2.3, ExecutableType Instance for ForLoop, the number of times that the <b>Variable</b> element can occur was clarified.</p> <p>Changed from:</p> <pre>&lt;xss:element name="Variable" type="DTS:VariableType"     maxOccurs="unbounded"/&gt;</pre> <p>Changed to:</p> <pre>&lt;xss:element name="Variable" type="DTS:VariableType"     minOccurs="0" maxOccurs="unbounded"/&gt;</pre>                                    |
| 2021/09/21        | <p>In section 2.6.4.2, ExecutableType Instance for Check Integrity Task, the end tag was added to the XSD for the <b>MaintenanceCheckIntegrityExe</b> element.</p> <p>Changed from:</p> <pre>    .     .     . &lt;/xs:simpleType&gt; &lt;/xs:attribute&gt; &lt;xs:attribute name="ThreadHint" use="optional" type="xs:int"/&gt; &lt;/xs:complexType&gt;</pre> <p>Changed to:</p> <pre>    .     .     . &lt;/xs:simpleType&gt; &lt;/xs:attribute&gt; &lt;xs:attribute name="ThreadHint" use="optional" type="xs:int"/&gt; &lt;/xs:complexType&gt; &lt;/xs:element&gt;</pre> |
| 2021/09/21        | <p>In section 2.6.4.6, ExecutableType Instance for Notify Operator Task, the name of the <b>OperatorNotifyList</b> element was clarified.</p> <p>Changed from:</p>   |

| Errata Published*   | Description   |  |                 |             |                     |                                   |  |       |       |       |
|---------------------|---|--|-----------------|-------------|---------------------|-----------------------------------|--|-------|-------|-------|
|                     | <ul style="list-style-type: none"> <li>▪ . . . This instance of the <b>SqlTaskData</b> element MUST NOT contain elements except for the <b>NotifyOperator</b> element. . . .</li> </ul> <p>Changed to:</p> <ul style="list-style-type: none"> <li>▪ . . . This instance of the <b>SqlTaskData</b> element MUST NOT contain elements except for the <b>OperatorNotifyList</b> element. . . .</li> </ul>  |  |                 |             |                     |                                   |  |       |       |       |
| 2021/09/21          | <p>In section 2.7.1.1.1.3.1, PipelineComponentInputType, the <b>properties</b> element was added to the XSD and the table.</p> <p>Changed from:</p> <pre data-bbox="518 777 1356 1058">&lt;xs:complexType name="PipelineComponentInputType"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="inputColumns"       type="DTS:PipelineComponentInputColumnsType"       minOccurs="0" form="unqualified"/&gt;     &lt;xs:element name="externalMetadataColumns"       type="DTS:PipelineComponentMetadataColumnsType"       minOccurs="0" form="unqualified"/&gt;   &lt;/xs:sequence&gt;   &lt;xs:attributeGroup     ref="DTS:PipelineComponentInputOutputElementAttributeGroup"/&gt; &lt;/xs:complexType&gt;</pre> <p>The following table specifies the elements of the <b>PipelineComponentInputType</b> type.</p> <table border="1" data-bbox="458 1142 1416 1402"> <thead> <tr> <th data-bbox="458 1142 665 1184">Element</th><th data-bbox="665 1142 1095 1184">Type definition</th><th data-bbox="1095 1142 1416 1184">Description</th></tr> </thead> <tbody> <tr> <td data-bbox="458 1184 665 1347"><b>inputColumns</b></td><td data-bbox="665 1184 1095 1347">PipelineComponentInputColumnsType</td><td data-bbox="1095 1184 1416 1347">A complex type that specifies a collection of input columns that are associated with the <b>input</b> element.</td></tr> <tr> <td data-bbox="458 1347 665 1402">. . .</td><td data-bbox="665 1347 1095 1402">. . .</td><td data-bbox="1095 1347 1416 1402">. . .</td></tr> </tbody> </table> <p>Changed to:</p> <pre data-bbox="518 1480 1356 1835">&lt;xs:complexType name="PipelineComponentInputType"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="properties"       type="DTS:PipelineComponentInputPropertiesType"       minOccurs="0" form="unqualified"/&gt;     &lt;xs:element name="inputColumns"       type="DTS:PipelineComponentInputColumnsType"       minOccurs="0" form="unqualified"/&gt;     &lt;xs:element name="externalMetadataColumns"       type="DTS:PipelineComponentMetadataColumnsType"       minOccurs="0" form="unqualified"/&gt;   &lt;/xs:sequence&gt;   &lt;xs:attributeGroup     ref="DTS:PipelineComponentInputOutputElementAttributeGroup"/&gt;</pre> | Element  | Type definition | Description | <b>inputColumns</b> | PipelineComponentInputColumnsType | A complex type that specifies a collection of input columns that are associated with the <b>input</b> element. | . . . | . . . | . . . |
| Element             | Type definition   | Description  |                 |             |                     |                                   |  |       |       |       |
| <b>inputColumns</b> | PipelineComponentInputColumnsType   | A complex type that specifies a collection of input columns that are associated with the <b>input</b> element. |                 |             |                     |                                   |  |       |       |       |
| . . .               | . . .   | . . .  |                 |             |                     |                                   |  |       |       |       |

| Errata Published*   | Description  |  |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
|---------------------|--|--|-----------------|-------------|-------------------|--------------------------------------|---|---------------------|-----------------------------------|--|-----|-----|-----|
|                     | <p>&lt;/xs:complexType&gt;</p> <p>The following table specifies the elements of the <b>PipelineComponentInputType</b> type.</p> <table border="1" data-bbox="463 382 1416 768"> <thead> <tr> <th data-bbox="463 382 654 424">Element</th><th data-bbox="654 382 1122 424">Type definition</th><th data-bbox="1122 382 1416 424">Description</th></tr> </thead> <tbody> <tr> <td data-bbox="463 424 654 557"><b>properties</b></td><td data-bbox="654 424 1122 557">PipelineComponentInputPropertiesType</td><td data-bbox="1122 424 1416 557">A complex type that specifies a collection of properties for an <b>input</b> element.</td></tr> <tr> <td data-bbox="463 557 654 720"><b>inputColumns</b></td><td data-bbox="654 557 1122 720">PipelineComponentInputColumnsType</td><td data-bbox="1122 557 1416 720">A complex type that specifies a collection of input columns that are associated with the <b>input</b> element.</td></tr> <tr> <td data-bbox="463 720 654 768">...</td><td data-bbox="654 720 1122 768">...</td><td data-bbox="1122 720 1416 768">...</td></tr> </tbody> </table> | Element  | Type definition | Description | <b>properties</b> | PipelineComponentInputPropertiesType | A complex type that specifies a collection of properties for an <b>input</b> element. | <b>inputColumns</b> | PipelineComponentInputColumnsType | A complex type that specifies a collection of input columns that are associated with the <b>input</b> element. | ... | ... | ... |
| Element             | Type definition  | Description  |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
| <b>properties</b>   | PipelineComponentInputPropertiesType   | A complex type that specifies a collection of properties for an <b>input</b> element.                          |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
| <b>inputColumns</b> | PipelineComponentInputColumnsType  | A complex type that specifies a collection of input columns that are associated with the <b>input</b> element. |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
| ...                 | ...  | ...  |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
| 2021/09/21          | <p>In section 2.7.1.11.1.1.1.1, SqlTaskDatabaseSelectionTypeEnum, the name of the applicable attribute was clarified.</p> <p>Changed from:</p> <p>The <b>SqlTaskDatabaseSelectionTypeEnum</b> type contains the enumeration values for the <b>SelectionType</b> attribute.</p> <p>Changed to:</p> <p>The <b>SqlTaskDatabaseSelectionTypeEnum</b> type contains the enumeration values for the <b>DatabaseSelectionType</b> attribute.</p>  |  |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
| 2021/09/21          | <p>In section 2.7.1.11.1.1.1.8, SqlTaskBaseAttributeGroup, the type of the <b>Connection</b> attribute was clarified.</p> <p>Changed from:</p> <pre data-bbox="551 1438 1192 1465">&lt;xs:attribute name="Connection" type="xs:string"/&gt;</pre> <p>Changed to:</p> <pre data-bbox="551 1564 1181 1592">&lt;xs:attribute name="Connection" type="DTS:uuid"/&gt;</pre>   |  |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |
| 2021/09/21          | <p>In section 2.7.1.11.1.1.1.10, BackupTaskAttributeGroup, the type of the <b>BackupCompressionAction</b> attribute was clarified.</p> <p>Changed from:</p> <pre data-bbox="551 1805 1122 1833">&lt;xs:attribute name="BackupCompressionAction"</pre>  |  |                 |             |                   |                                      |   |                     |                                   |  |     |     |     |

| Errata Published* | Description  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
|-------------------|--|-----------|-------------|-----|-----|------------------|--|-----|-----|-----------|-------------|-----|-----|------------------|---|-----|-----|
|                   | <p style="text-align: right;">type="SQLTask:BackupCompressionEnum"/&gt;</p> <p>Changed to:</p> <pre style="margin-left: 40px;">&lt;xs:attribute name="BackupCompressionAction"     type="SQLTask:BackupCompressionActionEnum"/&gt;</pre>   |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| 2021/09/21        | <p>In section 2.7.1.13, FtpDataObjectDataType, the type of the <b>TaskOperationType</b> attribute was clarified.</p> <p>Changed from:</p> <pre style="margin-left: 40px;">&lt;xs:attribute name="TaskOperationType" type="xs:string"</pre> <p>Changed to:</p> <pre style="margin-left: 40px;">&lt;xs:attribute name="TaskOperationType"     type="DTS:FtpDataTaskOperationTypeEnum"</pre>  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| 2021/09/21        | <p>In section 2.7.1.15.3, ScriptProjectBreakpointType, the description of the <b>Condition</b> attribute was clarified.</p> <p>Changed from:</p> <table border="1" data-bbox="463 1079 1421 1353"> <thead> <tr> <th data-bbox="463 1079 605 1136">Attribute</th><th data-bbox="605 1079 1421 1136">Description</th></tr> </thead> <tbody> <tr> <td data-bbox="463 1136 605 1193">...</td><td data-bbox="605 1136 1421 1193">...</td></tr> <tr> <td data-bbox="463 1193 605 1311"><b>Condition</b></td><td data-bbox="605 1193 1421 1311">A string value that specifies a condition that can be evaluated as a Boolean, to determine whether the breakpoint is fired. Whether the breakpoint is fired depends upon this <b>Condition</b> value and upon the values of the attributes <b>ConditionType</b>, <b>HitCount</b>, and <b>HitType</b>.</td></tr> <tr> <td data-bbox="463 1311 605 1353">...</td><td data-bbox="605 1311 1421 1353">...</td></tr> </tbody> </table> <p>Changed to:</p> <table border="1" data-bbox="463 1438 1421 1733"> <thead> <tr> <th data-bbox="463 1438 605 1495">Attribute</th><th data-bbox="605 1438 1421 1495">Description</th></tr> </thead> <tbody> <tr> <td data-bbox="463 1495 605 1552">...</td><td data-bbox="605 1495 1421 1552">...</td></tr> <tr> <td data-bbox="463 1552 605 1691"><b>Condition</b></td><td data-bbox="605 1552 1421 1691">A string value that specifies a condition that can be evaluated as a Boolean, to determine whether the breakpoint is fired. Whether the breakpoint is fired depends upon this <b>Condition</b> value and upon the values of the attributes <b>ConditionType</b>, <b>HitCount</b>, and <b>HitCountType</b>.</td></tr> <tr> <td data-bbox="463 1691 605 1733">...</td><td data-bbox="605 1691 1421 1733">...</td></tr> </tbody> </table> | Attribute | Description | ... | ... | <b>Condition</b> | A string value that specifies a condition that can be evaluated as a Boolean, to determine whether the breakpoint is fired. Whether the breakpoint is fired depends upon this <b>Condition</b> value and upon the values of the attributes <b>ConditionType</b> , <b>HitCount</b> , and <b>HitType</b> . | ... | ... | Attribute | Description | ... | ... | <b>Condition</b> | A string value that specifies a condition that can be evaluated as a Boolean, to determine whether the breakpoint is fired. Whether the breakpoint is fired depends upon this <b>Condition</b> value and upon the values of the attributes <b>ConditionType</b> , <b>HitCount</b> , and <b>HitCountType</b> . | ... | ... |
| Attribute         | Description  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| ...               | ...  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| <b>Condition</b>  | A string value that specifies a condition that can be evaluated as a Boolean, to determine whether the breakpoint is fired. Whether the breakpoint is fired depends upon this <b>Condition</b> value and upon the values of the attributes <b>ConditionType</b> , <b>HitCount</b> , and <b>HitType</b> .   |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| ...               | ...  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| Attribute         | Description  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| ...               | ...  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| <b>Condition</b>  | A string value that specifies a condition that can be evaluated as a Boolean, to determine whether the breakpoint is fired. Whether the breakpoint is fired depends upon this <b>Condition</b> value and upon the values of the attributes <b>ConditionType</b> , <b>HitCount</b> , and <b>HitCountType</b> .  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| ...               | ...  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |
| 2021/09/21        | In section 2.7.1.16.1.1.1, SendMailTaskType, the type of the <b>SMTPServer</b> attribute was clarified.  |           |             |     |     |                  |  |     |     |           |             |     |     |                  |   |     |     |

| Errata Published* | Description  |
|-------------------|--|
|                   | <p>Changed from:</p> <pre data-bbox="551 361 1192 388">&lt;xs:attribute name="SMTPServer" type="xs:string"/&gt;</pre> <p>Changed to:</p> <pre data-bbox="551 487 1181 515">&lt;xs:attribute name="SMTPServer" type="DTS:uuid"/&gt;</pre>   |
| 2021/09/21        | <p>In section 2.8.4.1, VariablePropertyNameEnum, the start tag was added to the XSD.</p> <p>Changed from:</p> <pre data-bbox="551 705 1181 783">&lt;xs:union memberTypes="DTS:BasePropertyNameEnum"&gt;   &lt;xs:simpleType&gt;     . . .</pre> <p>Changed to:</p> <pre data-bbox="518 882 1181 960">&lt;xs:simpleType name="VariablePropertyNameEnum"&gt;   &lt;xs:union memberTypes="DTS:BasePropertyNameEnum"&gt;     &lt;xs:simpleType&gt;       . . .</pre>   |
| 2021/09/21        | <p>In section 2.9.6, SourceTypeEnum, the name of the type was clarified in the XSD.</p> <p>Changed from:</p> <pre data-bbox="518 1176 1090 1201">&lt;xs:simpleType name="SqlStmtSourceTypeEnum"&gt;</pre> <p>Changed to:</p> <pre data-bbox="518 1300 1002 1326">&lt;xs:simpleType name="SourceTypeEnum"&gt;</pre>   |
| 2021/09/21        | <p>In section 5.1, DTS XSD, the <b>maxOccurs</b> attribute was removed from the <b>VariableValue</b> element of the <b>VariableType</b> complex type.</p> <p>Changed from:</p> <pre data-bbox="518 1543 1299 1643">&lt;xs:complexType name="VariableType"&gt;   . .     &lt;xs:element name="VariableValue" maxOccurs="unbounded" &gt;     . . .</pre> <p>Changed to:</p> <pre data-bbox="518 1742 1002 1841">&lt;xs:complexType name="VariableType"&gt;   . .     &lt;xs:element name="VariableValue"&gt;     . . .</pre> |

| Errata Published* | Description  |
|-------------------|--|
| 2021/09/21        | <p>In section 5.1, DTS XSD, the type was clarified for various attributes of the <b>TransferSqlServerObjectsTaskDataObjectType</b> complex type, and the schema definition for the <b>ListString</b> type was removed.</p> <p>Changed from:</p> <pre> &lt;xs:complexType name="TransferSqlServerObjectsTaskDataObjectType"&gt;     .     .     &lt;xs:attribute name="LoginsList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="UsersList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="RulesList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="TablesList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="ViewsList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="StoredProceduresList"         type="DTS&gt;ListStringType" form="unqualified"/&gt;     &lt;xs:attribute name="UserDefinedFunctionsList"         type="DTS&gt;ListStringType" form="unqualified"/&gt;     &lt;xs:attribute name="DefaultsList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="UserDefinedDataTypesList"         type="DTS&gt;ListStringType" form="unqualified"/&gt;     &lt;xs:attribute name="PartitionFunctionsList"         type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="PartitionSchemesList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="SchemasList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="SqlAssembliesList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="UserDefinedAggregatesList"         type="DTS&gt;ListStringType" form="unqualified"/&gt;     &lt;xs:attribute name="UserDefinedTypesList" type="DTS&gt;ListStringType"         form="unqualified"/&gt;     &lt;xs:attribute name="XmlSchemaCollectionsList"         type="DTS&gt;ListStringType"         form="unqualified"/&gt;     .     .     &lt;xs:attribute name="CopyAllDRIObjects" type="xs:boolean"         form="unqualified"/&gt; &lt;/xs:complexType&gt;  &lt;xs:simpleType name="ListStringType"&gt;     &lt;xs:restriction base="xs:string"&gt;         &lt;xs:pattern value="[0-9]+,[?([0-9]+,.+){0,}]" /&gt;     &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;  &lt;xs:simpleType name="TransferSqlServerObjectsTaskExistingDataEnum"&gt;     .     . </pre> <p>Changed to:</p> <pre> &lt;xs:complexType name="TransferSqlServerObjectsTaskDataObjectType"&gt;     .     .     &lt;xs:attribute name="LoginsList" type="xs:string"         form="unqualified"/&gt;     &lt;xs:attribute name="UsersList" type="xs:string"         form="unqualified"/&gt;     &lt;xs:attribute name="RulesList" type="xs:string"         form="unqualified"/&gt; </pre> |

| Errata Published* | Description  |
|-------------------|--|
|                   | <pre>         form="unqualified"/&gt; &lt;xs:attribute name="TablesList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="ViewsList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="StoredProceduresList"         type="xs:string" form="unqualified"/&gt; &lt;xs:attribute name="UserDefinedFunctionsList"         type="xs:string" form="unqualified"/&gt; &lt;xs:attribute name="DefaultsList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="UserDefinedDataTypesList"         type="xs:string" form="unqualified"/&gt; &lt;xs:attribute name="PartitionFunctionsList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="PartitionSchemesList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="SchemasList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="SqlAssembliesList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="UserDefinedAggregatesList"         type="xs:string" form="unqualified"/&gt; &lt;xs:attribute name="UserDefinedTypesList" type="xs:string"         form="unqualified"/&gt; &lt;xs:attribute name="XmlSchemaCollectionsList" type="xs:string"         form="unqualified"/&gt;         .         .         . &lt;xs:attribute name="CopyAllDRIObjects" type="xs:boolean"         form="unqualified"/&gt; &lt;/xs:complexType&gt; &lt;xs:simpleType name="TransferSqlServerObjectsTaskExistingDataEnum"&gt;         .         .         . </pre> |
| 2021/09/21        | <p>In section 5.1, DTS XSD, the <b>name</b> attribute was added to the <b>PipelineComponentPropertyAttributeGroup</b> group.</p> <p>Changed from:</p> <pre> &lt;xs:attributeGroup     name="PipelineComponentPropertyAttributeGroup"&gt;     &lt;xs:attribute name="id" type="xs:string" form="unqualified"/&gt;     &lt;xs:attribute name="dataType"         type="DTS:PipelineComponentDataTypeEnum"         form="unqualified"/&gt;     &lt;xs:attribute name="state"         type="DTS:PipelineComponentStateEnum"         form="unqualified"/&gt;         .         . </pre> <p>Changed to:</p> <pre> &lt;xs:attributeGroup     name="PipelineComponentPropertyAttributeGroup"&gt;     &lt;xs:attribute name="id" type="xs:string" form="unqualified"/&gt;     &lt;xs:attribute name="dataType"         type="DTS:PipelineComponentDataTypeEnum"         form="unqualified"/&gt;     &lt;xs:attribute name="name"         type="xs:string"         form="unqualified"/&gt;     &lt;xs:attribute name="state" </pre>   |

| Errata<br>Published* | Description   |
|----------------------|---|
|                      | <pre>type="DTS:PipelineComponentStateEnum" form="unqualified"/&gt; . . . </pre>   |
| 2021/09/21           | <p>In section 5.1, DTS XSD, the enumeration values of the <b>DtsDataTypeEnum</b> type were clarified.</p> <p>Changed from:</p> <pre>&lt;xs:simpleType name="DtsDataTypeEnum"&gt;   &lt;xs:restriction base="xs:int"&gt;     &lt;xs:enumeration value="2"/&gt;     &lt;xs:enumeration value="3"/&gt;     &lt;xs:enumeration value="4"/&gt;     &lt;xs:enumeration value="5"/&gt;     &lt;xs:enumeration value="6"/&gt;     &lt;xs:enumeration value="7"/&gt;     &lt;xs:enumeration value="8"/&gt;     &lt;xs:enumeration value="11"/&gt;     &lt;xs:enumeration value="13"/&gt;     &lt;xs:enumeration value="16"/&gt;     &lt;xs:enumeration value="17"/&gt;     &lt;xs:enumeration value="18"/&gt;     &lt;xs:enumeration value="19"/&gt;     &lt;xs:enumeration value="20"/&gt;     &lt;xs:enumeration value="21"/&gt;     &lt;xs:enumeration value="22"/&gt;     &lt;xs:enumeration value="23"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre> <p>Changed to:</p> <pre>&lt;xs:simpleType name="DtsDataTypeEnum"&gt;   &lt;xs:restriction base="xs:int"&gt;     &lt;xs:enumeration value="1"/&gt;     &lt;xs:enumeration value="2"/&gt;     &lt;xs:enumeration value="3"/&gt;     &lt;xs:enumeration value="4"/&gt;     &lt;xs:enumeration value="5"/&gt;     &lt;xs:enumeration value="6"/&gt;     &lt;xs:enumeration value="7"/&gt;     &lt;xs:enumeration value="8"/&gt;     &lt;xs:enumeration value="11"/&gt;     &lt;xs:enumeration value="13"/&gt;     &lt;xs:enumeration value="14"/&gt;     &lt;xs:enumeration value="16"/&gt;     &lt;xs:enumeration value="17"/&gt;     &lt;xs:enumeration value="18"/&gt;     &lt;xs:enumeration value="19"/&gt;     &lt;xs:enumeration value="20"/&gt;     &lt;xs:enumeration value="21"/&gt;     &lt;xs:enumeration value="22"/&gt;     &lt;xs:enumeration value="23"/&gt;     &lt;xs:enumeration value="64"/&gt;     &lt;xs:enumeration value="72"/&gt;     &lt;xs:enumeration value="129"/&gt;     &lt;xs:enumeration value="130"/&gt;     &lt;xs:enumeration value="131"/&gt;     &lt;xs:enumeration value="133"/&gt;     &lt;xs:enumeration value="134"/&gt;     &lt;xs:enumeration value="135"/&gt;     &lt;xs:enumeration value="139"/&gt;</pre> |

| Errata Published* | Description  |
|-------------------|--|
|                   | <pre data-bbox="530 280 954 375">&lt;xs:enumeration value="145"/&gt; &lt;xs:enumeration value="146"/&gt; &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>  |
| 2021/09/21        | <p>In section 5.1, DTS XSD, the pattern value of the <b>uuid</b> type was clarified.</p> <p>Changed from:</p> <pre data-bbox="514 566 1428 734">&lt;xs:simpleType name="uuid"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value="\{[0-9a-zA-Z]\{8\}-[0-9a-zA-Z]\{4\}-[0-9a-zA-Z]\{4\}-[0-9a-zA-Z]\{4\}-[0-9a-zA-Z]\{12\}\}" /&gt;     &lt;xs:pattern value="" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre> <p>Changed to:</p> <pre data-bbox="505 851 1428 977">&lt;xs:simpleType name="uuid"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:pattern value="\{[0-9a-zA-Z]\{8\}-[0-9a-zA-Z]\{4\}-[0-9a-zA-Z]\{4\}-[0-9a-zA-Z]\{4\}-[0-9a-zA-Z]\{12\}\}" /&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>             |
| 2021/09/21        | <p>In section 5.2, WebServiceTask XSD, the "File" enumeration value of the <b>WebServiceTaskDataOutputTypeEnum</b> type was clarified.</p> <p>Changed from:</p> <pre data-bbox="522 1199 1232 1347">&lt;xs:simpleType name="WebServiceTaskDataOutputTypeEnum"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:enumeration value="FileConnection"/&gt;     &lt;xs:enumeration value="Variable"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre> <p>Changed to:</p> <pre data-bbox="522 1442 1232 1590">&lt;xs:simpleType name="WebServiceTaskDataOutputTypeEnum"&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:enumeration value="File"/&gt;     &lt;xs:enumeration value="Variable"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre> |
| 2021/09/21        | <p>In section 5.6, Exec80PackageTask XSD, the type of the <b>PackageID</b> and <b>PackageVersionGUID</b> attributes of the <b>Exec80PackageTaskType</b> type was clarified.</p> <p>Changed from:</p> <pre data-bbox="546 1801 1281 1854">&lt;xs:attribute name="PackageID" type="DTS:uuid"/&gt; &lt;xs:attribute name="PackageVersionGUID" type="DTS:uuid"/&gt;</pre>  |

| Errata<br>Published* | Description  |
|----------------------|--|
|                      | <p>Changed to:</p> <pre data-bbox="545 333 1295 386">&lt;xs:attribute name="PackageID" type="xs:string"/&gt; &lt;xs:attribute name="PackageVersionGUID" type="xs:string"/&gt;</pre>  |
| 2021/09/21           | <p>In section 5.8, SQLTask XSD, the type of the <b>SqlTaskData</b> element was clarified.</p> <p>Changed from:</p> <pre data-bbox="518 566 1312 618">&lt;xs:element name="SqlTaskData" type="SQLTask:SqlTaskDataElementBackupTaskType"/&gt;</pre> <p>Changed to:</p> <pre data-bbox="518 724 1090 777">&lt;xs:element name="SqlTaskData" type="SQLTask:SqlTaskDataType"/&gt;</pre> |

\*Date format: YYYY/MM/DD