

[MS-SQLXQUERY-Diff]:

SQL XQuery Standards Support Document

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (["this documentation"](#)) for protocols, file formats, [data portability, computer languages, and standards as well as overviews of the interaction among each of these technologies support. Additionally, overview documents cover inter-protocol relationships and interactions.](#)
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you [may can](#) make copies of it in order to develop implementations of the technologies [that are](#) described in [the Open Specifications- this documentation and may can](#) distribute portions of it in your implementations [using that use](#) these technologies or [in](#) your documentation as necessary to properly document the implementation. You [may can](#) also distribute in your implementation, with or without modification, any [schema, IDL's schemas, IDLs](#), or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the [Open Specifications- documentation.](#)
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that [may might](#) cover your implementations of the technologies described in the [Open Specifications- documentation.](#) Neither this notice nor Microsoft's delivery of [the this](#) documentation grants any licenses under those [patents](#) or any other Microsoft patents. However, a given Open [Specification may Specifications document might](#) be covered by [the](#) Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise.](#) If you would prefer a written license, or if the technologies described in [the Open Specifications this documentation](#) are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** [To see all of the protocols in scope under a specific license program and the associated patents, visit the Patent Map.](#)
- **Trademarks.** The names of companies and products contained in this documentation [may might](#) be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [-www.microsoft.com/trademarks.](http://www.microsoft.com/trademarks)
- **Fictitious Names.** The example companies, organizations, products, domain names, [e-mail email](#) addresses, logos, people, places, and events [that are](#) depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than [as](#) specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications [documentation does](#) not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications [documents](#) are intended for use in conjunction with publicly available [standard standards](#) specifications and network programming art, and [assumes, as such, assume](#) that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. [For questions and support, please contact dochelp@microsoft.com.](#)

Revision Summary

Date	Revision History	Revision Class	Comments
11/3/2011	0.1	New	Released new document.
1/19/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
2/23/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
3/27/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
5/24/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
6/29/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
10/23/2012	0.1	None	No changes to the meaning, language, or formatting of the technical content.
3/26/2013	0.1	None	No changes to the meaning, language, or formatting of the technical content.
6/11/2013	0.1	None	No changes to the meaning, language, or formatting of the technical content.
8/8/2013	0.1	None	No changes to the meaning, language, or formatting of the technical content.
12/5/2013	0.1	None	No changes to the meaning, language, or formatting of the technical content.
2/11/2014	0.1	None	No changes to the meaning, language, or formatting of the technical content.
5/20/2014	0.1	None	No changes to the meaning, language, or formatting of the technical content.
5/10/2016	1.0	None	No changes to the meaning, language, or formatting of the technical content.
<u>8/16/2017</u>	<u>1.0</u>	<u>None</u>	<u>No changes to the meaning, language, or formatting of the technical content.</u>

Table of Contents

1	Introduction	10
1.1	Glossary	10
1.2	References	10
1.2.1	Normative References	10
1.2.2	Informative References	11
1.3	Microsoft Implementations	11
1.4	Standards Support Requirements	11
1.5	Notation.....	11
2	Standards Support Statements.....	12
2.1	Normative Variations	12
2.1.1	Data Model Items	12
2.1.1.1	[XDM/2] Section 1 Introduction	12
2.1.1.2	Concepts.....	12
2.1.1.2.1	[XDM/2] Section 2.4 Document Order	12
2.1.1.3	Data Model Construction	12
2.1.1.3.1	[XDM/2] Section 3 Data Model Construction	12
2.1.1.3.2	[XDM/2] Section 3.1 Direct Construction	12
2.1.1.3.3	[XDM/2] Section 3.2 Construction from an Infoset.....	12
2.1.1.3.4	[XDM/2] Section 3.3 Construction from a PSVI.....	12
2.1.1.3.5	[XDM/2] Section 3.3.1 Mapping PSVI Additions to Node Properties	12
2.1.1.3.6	[XDM/2] Section 3.3.1.1 Element and Attribute Node Type Names	13
2.1.1.3.7	[XDM/2] Section 3.3.1.2 Typed Value Determination	13
2.1.1.3.8	[XDM/2] Section 3.3.1.3 Relationship Between Typed Value and String Value.....	13
2.1.1.3.9	[XDM/2] Section 3.3.1.4 Pattern Facets	13
2.1.1.3.10	[XDM/2] Section 3.3.3 QNames and NOTATIONS	13
2.1.1.4	Accessors.....	13
2.1.1.4.1	[XDM/2] Section5 Accessors	13
2.1.1.5	Nodes.....	13
2.1.1.5.1	[XDM/2] Section 6.2.4 Construction from a PSVI.....	13
2.1.1.5.2	[XDM/2] Section 6.4 Namespace Nodes	13
2.1.1.6	Conformance.....	13
2.1.1.6.1	[XDM/2] Section 7 Conformance	13
2.1.2	Basics	14
2.1.2.1	Expression Context	14
2.1.2.1.1	[XQuery1.0/2] Section 2.1.1 Static Context	14
2.1.2.1.1.1	[XQuery1.0/2] Appendix C.1 Static Context Components	14
2.1.2.1.1.1.1	XPath 1.0 Compatibility Mode	14
2.1.2.1.1.1.2	Statically Known Namespaces	14
2.1.2.1.1.1.3	Default Function Namespace.....	14
2.1.2.1.1.1.4	In-Scope Schema Types.....	14
2.1.2.1.1.1.5	In-Scope Element Declarations.....	14
2.1.2.1.1.1.6	In-Scope Attribute Declarations.....	14
2.1.2.1.1.1.7	In-Scope Variables	14
2.1.2.1.1.1.8	Function Signatures	14
2.1.2.1.1.1.9	Statically Known Collations	15
2.1.2.1.1.1.10	Default Collation.....	15
2.1.2.1.1.1.11	Construction Mode.....	15
2.1.2.1.1.1.12	Ordering Mode	15
2.1.2.1.1.1.13	Default Order for Empty Sequences	15
2.1.2.1.1.1.14	Boundary-Space Policy	15
2.1.2.1.1.1.15	Copy-Namespaces Mode.....	15
2.1.2.1.1.1.16	Base URI.....	15
2.1.2.1.1.1.17	Statically Known Documents	15

2.1.2.1.1.18	Statically Known Collections.....	15
2.1.2.1.1.19	Statically Known Default Collection Type	15
2.1.2.1.2	[XQuery1.0/2] Section 2.1.2 Dynamic Context	16
2.1.2.1.2.1	[XQuery1.0/2] Appendix C.2 Dynamic Context Components.....	16
2.1.2.1.2.1.1	Variable Values	16
2.1.2.1.2.1.2	Function Implementations	16
2.1.2.1.2.1.3	Current dateTime	16
2.1.2.1.2.1.4	Implicit Timezone	16
2.1.2.1.2.1.5	Available Documents.....	16
2.1.2.1.2.1.6	Available Collections	16
2.1.2.1.2.1.7	Default Collection	16
2.1.2.2	Processing Model	16
2.1.2.2.1	[XQuery1.0/2] Section 2.2.1 Data Model Generation.....	16
2.1.2.2.2	[XQuery1.0/2] Section 2.2.2 Schema Import Processing	16
2.1.2.2.3	[XQuery1.0/2] Section 2.2.3.1 Expression Processing - Static Analysis Phase	16
2.1.2.2.4	[XQuery1.0/2] Section 2.2.3.2 Expression Processing - Dynamic Evaluation Phase	16
2.1.2.2.5	[XQuery1.0/2] Section 2.2.4 Serialization.....	17
2.1.2.2.6	[XQuery1.0/2] Section 2.2.5 Consistency Constraints	17
2.1.2.3	Error Handling	17
2.1.2.3.1	[XQuery1.0/2] Section 2.3.1 Kinds of Errors	17
2.1.2.3.2	[XQuery1.0/2] Section 2.3.2 Identifying and Reporting Errors.....	17
2.1.2.3.3	[XQuery1.0/2] Section 2.3.3 Handling Dynamic Errors	17
2.1.2.3.4	[XQuery1.0/2] Section 2.3.4 Errors and Optimization.....	17
2.1.2.4	Concepts.....	17
2.1.2.4.1	[XQuery1.0/2] Section 2.4.1 Document Order.....	17
2.1.2.4.2	[XQuery1.0/2] Section 2.4.2 Atomization	17
2.1.2.4.3	[XQuery1.0/2] Section 2.4.3 Effective Boolean Value	17
2.1.2.4.4	[XQuery1.0/2] Section 2.4.4 Input Sources	18
2.1.2.4.5	[XQuery1.0/2] Section 2.4.5 URI Literals.....	18
2.1.2.5	Types	18
2.1.2.5.1	[XQuery1.0/2] Section 2.5.1 Predefined Schema Types.....	18
2.1.2.5.2	[XQuery1.0/2] Section 2.5.3 SequenceType Syntax.....	18
2.1.2.5.3	[XQuery1.0/2] Section 2.5.4 SequenceType Matching	20
2.1.2.5.4	[XQuery1.0/2] Section 2.5.4.1 Matching a Sequence Type and a Value ..	20
2.1.2.5.5	[XQuery1.0/2] Section 2.5.4.2 Matching an Item Type and an Item.....	21
2.1.2.5.6	[XQuery1.0/2] Section 2.5.4.3 Element Test.....	21
2.1.2.5.7	[XQuery1.0/2] Section 2.5.4.4 Schema Element Test.....	21
2.1.2.5.8	[XQuery1.0/2] Section 2.5.4.5 Attribute Test.....	21
2.1.2.5.9	[XQuery1.0/2] Section 2.5.4.6 Schema Attribute Test.....	21
2.1.3	Data Types	21
2.1.3.1	XSD Types	21
2.1.3.1.1	xs:ID	21
2.1.3.1.2	xs:IDREF.....	21
2.1.3.1.3	xs:untypedAtomic	21
2.1.3.1.4	xs:untyped	21
2.1.3.1.5	xs:NOTATION	21
2.1.3.1.6	xs:yearMonthDuration.....	22
2.1.3.1.7	xs:dayTimeDuration	22
2.1.3.1.8	xs:IDREFS	22
2.1.3.2	Casting Primitive Type to Primitive Type	22
2.1.4	Expressions	22
2.1.4.1	Expression Syntax.....	22
2.1.4.1.1	[XQuery1.0/2] Section 3 Expressions.....	22
2.1.4.1.2	[XQuery1.0/2] Section 3.1 Primary Expressions	23
2.1.4.1.3	[XQuery1.0/2] Section 3.1.1 Literals.....	23
2.1.4.1.4	[XQuery1.0/2] Section 3.1.2 Variable References	23

2.1.4.1.5	[XQuery1.0/2]	Section 3.1.3 Parenthesized Expressions	24
2.1.4.1.6	[XQuery1.0/2]	Section 3.1.4 Context Item Expression	24
2.1.4.1.7	[XQuery1.0/2]	Section 3.1.5 Function Calls	24
2.1.4.1.8	[XQuery1.0/2]	Section 3.2 Path Expressions	24
2.1.4.1.9	[XQuery1.0/2]	Section 3.2.1 Steps	24
2.1.4.1.10	[XQuery1.0/2]	Section 3.2.1.1 Axes	25
2.1.4.1.11	[XQuery1.0/2]	Section 3.2.1.2 Node Tests.....	25
2.1.4.1.12	[XQuery1.0/2]	Section 3.2.2 Predicates	26
2.1.4.1.13	[XQuery1.0/2]	Section 3.2.3 Unabbreviated Syntax.....	26
2.1.4.1.14	[XQuery1.0/2]	Section 3.2.4 Abbreviated Syntax	26
2.1.4.1.15	[XQuery1.0/2]	Section 3.3.1 Constructing Sequences	26
2.1.4.1.16	[XQuery1.0/2]	Section 3.3.2 Filter Expressions	27
2.1.4.1.17	[XQuery1.0/2]	Section 3.3.3 Combining Node Sequences	27
2.1.4.1.18	[XQuery1.0/2]	Section 3.4 Arithmetic Expressions.....	27
2.1.4.1.19	[XQuery1.0/2]	Section 3.5 Comparison Expressions	28
2.1.4.1.20	[XQuery1.0/2]	Section 3.5.1 Value Comparisons	28
2.1.4.1.21	[XQuery1.0/2]	Section 3.5.2 General Comparisons	28
2.1.4.1.22	[XQuery1.0/2]	Section 3.5.3 Node Comparisons.....	28
2.1.4.1.23	[XQuery1.0/2]	Section 3.6 Logical Expressions	28
2.1.4.1.24	[XQuery1.0/2]	Section 3.7 Constructors	29
2.1.4.1.25	[XQuery1.0/2]	Section 3.7.1 Direct Element Constructors	30
2.1.4.1.26	[XQuery1.0/2]	Section 3.7.1.1 Attributes	31
2.1.4.1.27	[XQuery1.0/2]	Section 3.7.1.2 Namespace Declaration Attributes	31
2.1.4.1.28	[XQuery1.0/2]	Section 3.7.1.3 Content	31
2.1.4.1.29	[XQuery1.0/2]	Section 3.7.1.4 Boundary Whitespace.....	31
2.1.4.1.30	[XQuery1.0/2]	Section 3.7.2 Other Direct Constructors	31
2.1.4.1.31	[XQuery1.0/2]	Section 3.7.3 Computed Constructors.....	32
2.1.4.1.32	[XQuery1.0/2]	Section 3.7.3.1 Computed Element Constructors.....	32
2.1.4.1.33	[XQuery1.0/2]	Section 3.7.3.2 Computed Attribute Constructors.....	32
2.1.4.1.34	[XQuery1.0/2]	Section 3.7.3.3 Document Node Constructors	32
2.1.4.1.35	[XQuery1.0/2]	Section 3.7.3.4 Text Node Constructors	32
2.1.4.1.36	[XQuery1.0/2]	Section 3.7.3.5 Computed Processing Instruction Constructors	33
2.1.4.1.37	[XQuery1.0/2]	Section 3.7.3.6 Computed Comment Constructors	33
2.1.4.1.38	[XQuery1.0/2]	Section 3.7.4 In-scope Namespaces of a Constructed Element	33
2.1.4.1.39	[XQuery1.0/2]	Section 3.8 FLWOR Expressions	33
2.1.4.1.40	[XQuery1.0/2]	Section 3.8.1 For and Let Clauses	34
2.1.4.1.41	[XQuery1.0/2]	Section 3.8.2 Where Clause.....	34
2.1.4.1.42	[XQuery1.0/2]	Section 3.8.3 Order By and Return Clauses	34
2.1.4.1.43	[XQuery1.0/2]	Section 3.9 Ordered and Unordered Expressions	34
2.1.4.1.44	[XQuery1.0/2]	Section 3.10 Conditional Expressions.....	35
2.1.4.1.45	[XQuery1.0/2]	Section 3.11 Quantified Expressions	35
2.1.4.1.46	[XQuery1.0/2]	Section 3.12.1 Instance Of.....	35
2.1.4.1.47	[XQuery1.0/2]	Section 3.12.2 Typeswitch	35
2.1.4.1.48	[XQuery1.0/2]	Section 3.12.3 Cast.....	36
2.1.4.1.49	[XQuery1.0/2]	Section 3.12.4 Castable	36
2.1.4.1.50	[XQuery1.0/2]	Section 3.12.5 Constructor Functions	36
2.1.4.1.51	[XQuery1.0/2]	Section 3.12.6 Treat.....	36
2.1.4.1.52	[XQuery1.0/2]	Section 3.13 Validate Expressions	36
2.1.4.1.53	[XQuery1.0/2]	Section 3.14 Extension Expressions.....	37
2.1.4.1.54	[XQuery1.0/2]	Appendix A.1 EBNF	37
2.1.4.2		Modules and Prologs.....	37
2.1.4.2.1	[XQuery1.0/2]	Section 4 Modules and Prologs.....	37
2.1.4.2.2	[XQuery1.0/2]	Section 4.1 Version Declaration	38
2.1.4.2.3	[XQuery1.0/2]	Section 4.2 Module Declaration	38
2.1.4.2.4	[XQuery1.0/2]	Section 4.3 Boundary-space Declaration	38
2.1.4.2.5	[XQuery1.0/2]	Section 4.4 Default Collation Declaration.....	39

2.1.4.2.6	[XQuery1.0/2]	Section 4.5 Base URI Declaration	39
2.1.4.2.7	[XQuery1.0/2]	Section 4.6 Construction Declaration	39
2.1.4.2.8	[XQuery1.0/2]	Section 4.7 Ordering Mode Declaration	39
2.1.4.2.9	[XQuery1.0/2]	Section 4.8 Empty Order Declaration	39
2.1.4.2.10	[XQuery1.0/2]	Section 4.9 Copy-Namespaces Declaration	39
2.1.4.2.11	[XQuery1.0/2]	Section 4.10 Schema Import	40
2.1.4.2.12	[XQuery1.0/2]	Section 4.11 Module Import	40
2.1.4.2.13	[XQuery1.0/2]	Section 4.12 Namespace Declaration	40
2.1.4.2.14	[XQuery1.0/2]	Section 4.13 Default Namespace Declaration	40
2.1.4.2.15	[XQuery1.0/2]	Section 4.14 Variable Declaration	40
2.1.4.2.16	[XQuery1.0/2]	Section 4.15 Function Declaration	41
2.1.4.2.17	[XQuery1.0/2]	Section 4.16 Option Declaration	41
2.1.5	Operators		41
2.1.5.1	Numeric Operators		41
2.1.5.1.1	[XQuery1.0XPath2.0/2]	Section 6.2.4 op:numeric-divide	41
2.1.5.1.2	[XQuery1.0XPath2.0/2]	Section 6.2.5 op:numeric-integer-divide	42
2.1.5.2	String Operators		42
2.1.5.3	anyURI Operators		42
2.1.5.4	Boolean Operators		42
2.1.5.4.1	[XQuery1.0XPath2.0/2]	Section 9.2.2 op:boolean-less-than	42
2.1.5.4.2	[XQuery1.0XPath2.0/2]	Section 9.2.3 op:boolean-greater-than	42
2.1.5.5	Durations, Dates, and Times Operators		42
2.1.5.5.1	[XQuery1.0XPath2.0/2]	Section 10.4.1 op:yearMonthDuration-less-than	42
2.1.5.5.2	[XQuery1.0XPath2.0/2]	Section 10.4.2 op:yearMonthDuration-greater-than	42
2.1.5.5.3	[XQuery1.0XPath2.0/2]	Section 10.4.3 op:dayTimeDuration-less-than	42
2.1.5.5.4	[XQuery1.0XPath2.0/2]	Section 10.4.4 op:dayTimeDuration-greater-than	42
2.1.5.5.5	[XQuery1.0XPath2.0/2]	Section 10.4.6 op:dateEqual	42
2.1.5.5.6	[XQuery1.0XPath2.0/2]	Section 10.4.8 op:date-greater-than	42
2.1.5.5.7	[XQuery1.0XPath2.0/2]	Section 10.4.9 op:date-equal	43
2.1.5.5.8	[XQuery1.0XPath2.0/2]	Section 10.4.10 op:date-less-than	43
2.1.5.5.9	[XQuery1.0XPath2.0/2]	Section 10.4.12 op:time-equal	43
2.1.5.5.10	[XQuery1.0XPath2.0/2]	Section 10.6.1 op:add-yearMonthDurations	43
2.1.5.5.11	[XQuery1.0XPath2.0/2]	Section 10.6.2 op:subtract-yearMonthDurations	43
2.1.5.5.12	[XQuery1.0XPath2.0/2]	Section 10.6.3 op:multiply-yearMonthDuration	43
2.1.5.5.13	[XQuery1.0XPath2.0/2]	Section 10.6.4 op:divide-yearMonthDuration	43
2.1.5.5.14	[XQuery1.0XPath2.0/2]	Section 10.6.5 op:divide-yearMonthDuration-by-yearMonthDuration	43
2.1.5.5.15	[XQuery1.0XPath2.0/2]	Section 10.6.6 op:add-dayTimeDurations	43
2.1.5.5.16	[XQuery1.0XPath2.0/2]	Section 10.6.7 op:subtract-dayTimeDurations	43
2.1.5.5.17	[XQuery1.0XPath2.0/2]	Section 10.6.8 op:multiply-dayTimeDuration	43
2.1.5.5.18	[XQuery1.0XPath2.0/2]	Section 10.6.9 op:divide-dayTimeDuration	43
2.1.5.5.19	[XQuery1.0XPath2.0/2]	Section 10.6.10 op:divide-dayTimeDuration-by-dayTimeDuration	44
2.1.5.5.20	[XQuery1.0XPath2.0/2]	Section 10.8.4 op:add-yearMonthDuration-to-dateTime	44
2.1.5.5.21	[XQuery1.0XPath2.0/2]	Section 10.8.5 op:add-dayTimeDuration-to-dateTime	44
2.1.5.5.22	[XQuery1.0XPath2.0/2]	Section 10.8.6 op:subtract-yearMonthDuration-from-dateTime	44
2.1.5.5.23	[XQuery1.0XPath2.0/2]	Section 10.8.7 op:subtract-dayTimeDuration-from-dateTime	44
2.1.5.5.24	[XQuery1.0XPath2.0/2]	Section 10.8.8 op:add-yearMonthDuration-to-date	44
2.1.5.5.25	[XQuery1.0XPath2.0/2]	Section 10.8.9 op:add-dayTimeDuration-to-date	44
2.1.5.5.26	[XQuery1.0XPath2.0/2]	Section 10.8.10 op:subtract-yearMonthDuration-from-date	44

2.1.5.5.27	[XQuery1.0XPath2.0/2] Section 10.8.11 op:subtract-dayTimeDuration-from-date.....	44
2.1.5.5.28	[XQuery1.0XPath2.0/2] Section 10.8.12 op:add-dayTimeDuration-to-time.....	45
2.1.5.5.29	[XQuery1.0XPath2.0/2] Section 10.8.13 op:subtract-dayTimeDuration-from-time.....	45
2.1.5.6	Notation Operators.....	45
2.1.5.6.1	[XQuery1.0XPath2.0/2] Section 13.1.1 op:NOTATION-equal.....	45
2.1.5.7	Sequences Operators.....	45
2.1.5.7.1	[XQuery1.0XPath2.0/2] Section 15.3.2 op:union.....	45
2.1.5.7.2	[XQuery1.0XPath2.0/2] Section 15.3.3 op:intersect.....	45
2.1.5.7.3	[XQuery1.0XPath2.0/2] Section 15.3.4 op:except.....	45
2.1.5.7.4	[XQuery1.0XPath2.0/2] Section 15.5.1 op:to.....	45
2.1.5.8	Context.....	45
2.1.6	Functions.....	45
2.1.6.1	Accessors.....	45
2.1.6.1.1	[XQuery1.0XPath2.0/2] Section 2.1 fn:node-name.....	45
2.1.6.1.2	[XQuery1.0XPath2.0/2] Section 2.2 fn:nilled.....	46
2.1.6.1.3	[XQuery1.0XPath2.0/2] Section 2.3 fn:string.....	46
2.1.6.1.4	[XQuery1.0XPath2.0/2] Section 2.5 fn:base-uri.....	46
2.1.6.1.5	[XQuery1.0XPath2.0/2] Section 2.6 fn:document-uri.....	46
2.1.6.2	Numeric Functions.....	46
2.1.6.2.1	[XQuery1.0XPath2.0/2] Section 6.4.1 fn:abs.....	46
2.1.6.2.2	[XQuery1.0XPath2.0/2] Section 6.4.2 fn:ceiling.....	46
2.1.6.2.3	[XQuery1.0XPath2.0/2] Section 6.4.3 fn:floor.....	46
2.1.6.2.4	[XQuery1.0XPath2.0/2] Section 6.4.4 fn:round.....	46
2.1.6.2.5	[XQuery1.0XPath2.0/2] Section 6.4.5 fn:round-half-to-even.....	47
2.1.6.3	String Functions.....	47
2.1.6.3.1	[XQuery1.0XPath2.0/2] Section 7.2.1 fn:codepoints-to-string.....	47
2.1.6.3.2	[XQuery1.0XPath2.0/2] Section 7.2.2 fn:string-to-codepoints.....	47
2.1.6.3.3	[XQuery1.0XPath2.0/2] Section 7.3.2 fn:compare.....	47
2.1.6.3.4	[XQuery1.0XPath2.0/2] Section 7.3.3 fn:codepoint-equal.....	47
2.1.6.3.5	[XQuery1.0XPath2.0/2] Section 7.4.1 fn:concat.....	47
2.1.6.3.6	[XQuery1.0XPath2.0/2] Section 7.4.2 fn:string-join.....	47
2.1.6.3.7	[XQuery1.0XPath2.0/2] Section 7.4.3 fn:substring.....	47
2.1.6.3.8	[XQuery1.0XPath2.0/2] Section 7.4.4 fn:string-length.....	47
2.1.6.3.9	[XQuery1.0XPath2.0/2] Section 7.4.5 fn:normalize-space.....	47
2.1.6.3.10	[XQuery1.0XPath2.0/2] Section 7.4.6 fn:normalize-unicode.....	47
2.1.6.3.11	[XQuery1.0XPath2.0/2] Section 7.4.9 fn:translate.....	48
2.1.6.3.12	[XQuery1.0XPath2.0/2] Section 7.4.10 fn:encode-for-uri.....	48
2.1.6.3.13	[XQuery1.0XPath2.0/2] Section 7.4.11 fn:iri-to-uri.....	48
2.1.6.3.14	[XQuery1.0XPath2.0/2] Section 7.4.12 fn:escape-html-uri.....	48
2.1.6.3.15	[XQuery1.0XPath2.0/2] Section 7.5.1 fn:contains.....	48
2.1.6.3.16	[XQuery1.0XPath2.0/2] Section 7.5.2 fn:starts-with.....	48
2.1.6.3.17	[XQuery1.0XPath2.0/2] Section 7.5.3 fn:ends-with.....	48
2.1.6.3.18	[XQuery1.0XPath2.0/2] Section 7.5.4 fn:substring-before.....	48
2.1.6.3.19	[XQuery1.0XPath2.0/2] Section 7.5.5 fn:substring-after.....	48
2.1.6.3.20	[XQuery1.0XPath2.0/2] Section 7.6.2 fn:matches.....	48
2.1.6.3.21	[XQuery1.0XPath2.0/2] Section 7.6.3 fn:replace.....	48
2.1.6.3.22	[XQuery1.0XPath2.0/2] Section 7.6.4 fn:tokenize.....	48
2.1.6.4	anyURI Functions.....	48
2.1.6.4.1	[XQuery1.0XPath2.0/2] Section 8.1 fn:resolve-uri.....	48
2.1.6.5	Durations, Dates, and Times Functions.....	49
2.1.6.5.1	[XQuery1.0XPath2.0/2] Section 10.5.1 fn:years-from-duration.....	49
2.1.6.5.2	[XQuery1.0XPath2.0/2] Section 10.5.2 fn:months-from-duration.....	49
2.1.6.5.3	[XQuery1.0XPath2.0/2] Section 10.5.3 fn:days-from-duration.....	49
2.1.6.5.4	[XQuery1.0XPath2.0/2] Section 10.5.4 fn:hours-from-duration.....	49
2.1.6.5.5	[XQuery1.0XPath2.0/2] Section 10.5.5 fn:minutes-from-duration.....	49

2.1.6.5.6	[XQuery1.0XPath2.0/2]	Section 10.5.6	fn:seconds-from-duration	49
2.1.6.5.7	[XQuery1.0XPath2.0/2]	Section 10.5.7	fn:year-from-dateTime	49
2.1.6.5.8	[XQuery1.0XPath2.0/2]	Section 10.5.8	fn:month-from-dateTime	49
2.1.6.5.9	[XQuery1.0XPath2.0/2]	Section 10.5.9	fn:day-from-dateTime	49
2.1.6.5.10	[XQuery1.0XPath2.0/2]	Section 10.5.10	fn:hours-from-dateTime	49
2.1.6.5.11	[XQuery1.0XPath2.0/2]	Section 10.5.11	fn:minutes-from-dateTime	49
2.1.6.5.12	[XQuery1.0XPath2.0/2]	Section 10.5.12	fn:seconds-from-dateTime	49
2.1.6.5.13	[XQuery1.0XPath2.0/2]	Section 10.5.13	fn:timezone-from-dateTime	49
2.1.6.5.14	[XQuery1.0XPath2.0/2]	Section 10.5.14	fn:year-from-date	49
2.1.6.5.15	[XQuery1.0XPath2.0/2]	Section 10.5.15	fn:month-from-date	50
2.1.6.5.16	[XQuery1.0XPath2.0/2]	Section 10.5.16	fn:day-from-date	50
2.1.6.5.17	[XQuery1.0XPath2.0/2]	Section 10.5.17	fn:timezone-from-date	50
2.1.6.5.18	[XQuery1.0XPath2.0/2]	Section 10.5.18	fn:hours-from-time	50
2.1.6.5.19	[XQuery1.0XPath2.0/2]	Section 10.5.19	fn:minutes-from-time	50
2.1.6.5.20	[XQuery1.0XPath2.0/2]	Section 10.5.20	fn:seconds-from-time	50
2.1.6.5.21	[XQuery1.0XPath2.0/2]	Section 10.5.21	fn:timezone-from-time	50
2.1.6.5.22	[XQuery1.0XPath2.0/2]	Section 10.7.1	fn:adjust-dateTime-to-timezone	50
2.1.6.5.23	[XQuery1.0XPath2.0/2]	Section 10.7.2	fn:adjust-date-to-timezone	50
2.1.6.5.24	[XQuery1.0XPath2.0/2]	Section 10.7.3	fn:adjust-time-to-timezone	50
2.1.6.6	QNames Functions			50
2.1.6.6.1	[XQuery1.0XPath2.0/2]	Section 11.1.1	fn:resolve-QName	50
2.1.6.6.2	[XQuery1.0XPath2.0/2]	Section 11.1.2	fn:QName	50
2.1.6.6.3	[XQuery1.0XPath2.0/2]	Section 11.2.2	fn:prefix-from-QName	50
2.1.6.6.4	[XQuery1.0XPath2.0/2]	Section 11.2.3	fn:local-name-from-QName	50
2.1.6.6.5	[XQuery1.0XPath2.0/2]	Section 11.2.5	fn:namespace-uri-for-prefix	51
2.1.6.6.6	[XQuery1.0XPath2.0/2]	Section 11.2.6	fn:in-scope-prefixes	51
2.1.6.7	base64Binary and hexBinary Functions			51
2.1.6.8	Notation Functions			51
2.1.6.9	Nodes Functions			51
2.1.6.9.1	[XQuery1.0XPath2.0/2]	Section 14.1	fn:name	51
2.1.6.9.2	[XQuery1.0XPath2.0/2]	Section 14.3	fn:namespace-uri	51
2.1.6.9.3	[XQuery1.0XPath2.0/2]	Section 14.4	fn:number	51
2.1.6.9.4	[XQuery1.0XPath2.0/2]	Section 14.5	fn:lang	51
2.1.6.9.5	[XQuery1.0XPath2.0/2]	Section 14.9	fn:root	51
2.1.6.10	Sequences Functions			51
2.1.6.10.1	[XQuery1.0XPath2.0/2]	Section 15.1.1	fn:boolean	51
2.1.6.10.2	[XQuery1.0XPath2.0/2]	Section 15.1.3	fn:index-of	51
2.1.6.10.3	[XQuery1.0XPath2.0/2]	Section 15.1.5	fn:exists	52
2.1.6.10.4	[XQuery1.0XPath2.0/2]	Section 15.1.6	fn:distinct-values	52
2.1.6.10.5	[XQuery1.0XPath2.0/2]	Section 15.1.7	fn:insert-before	52
2.1.6.10.6	[XQuery1.0XPath2.0/2]	Section 15.1.8	fn:remove	52
2.1.6.10.7	[XQuery1.0XPath2.0/2]	Section 15.1.9	fn:reverse	52
2.1.6.10.8	[XQuery1.0XPath2.0/2]	Section 15.1.10	fn:subsequence	52
2.1.6.10.9	[XQuery1.0XPath2.0/2]	Section 15.1.11	fn:unordered	52
2.1.6.10.10	[XQuery1.0XPath2.0/2]	Section 15.2.1	fn:zero-or-one	52
2.1.6.10.11	[XQuery1.0XPath2.0/2]	Section 15.2.2	fn:one-or-more	52
2.1.6.10.12	[XQuery1.0XPath2.0/2]	Section 15.2.3	fn:exactly-one	52
2.1.6.10.13	[XQuery1.0XPath2.0/2]	Section 15.3.1	fn:deep-equal	53
2.1.6.10.14	[XQuery1.0XPath2.0/2]	Section 15.4.2	fn:avg	53
2.1.6.10.15	[XQuery1.0XPath2.0/2]	Section 15.4.3	fn:max	53
2.1.6.10.16	[XQuery1.0XPath2.0/2]	Section 15.4.4	fn:min	53
2.1.6.10.17	[XQuery1.0XPath2.0/2]	Section 15.4.5	fn:sum	53
2.1.6.10.18	[XQuery1.0XPath2.0/2]	Section 15.5.2	fn:id	53
2.1.6.10.19	[XQuery1.0XPath2.0/2]	Section 15.5.3	fn:idref	53
2.1.6.10.20	[XQuery1.0XPath2.0/2]	Section 15.5.4	fn:doc	53
2.1.6.10.21	[XQuery1.0XPath2.0/2]	Section 15.5.5	fn:doc-available	54
2.1.6.10.22	[XQuery1.0XPath2.0/2]	Section 15.5.6	fn:collection	54
2.1.6.10.23	[XQuery1.0XPath2.0/2]	Section 15.5.7	fn:element-with-id	54

2.1.6.11	Context	54
2.1.6.11.1	[XQuery1.0XPath2.0/2] Section 16.1 fn:position	54
2.1.6.11.2	[XQuery1.0XPath2.0/2] Section 16.2 fn:last	54
2.1.6.11.3	[XQuery1.0XPath2.0/2] Section 16.3 fn:current-dateTime.....	54
2.1.6.11.4	[XQuery1.0XPath2.0/2] Section 16.4 fn:current-date.....	54
2.1.6.11.5	[XQuery1.0XPath2.0/2] Section 16.5 fn:current-time.....	54
2.1.6.11.6	[XQuery1.0XPath2.0/2] Section 16.6 fn:implicit-timezone	54
2.1.6.11.7	[XQuery1.0XPath2.0/2] Section 16.7 fn:default-collation.....	54
2.1.6.11.8	[XQuery1.0XPath2.0/2] Section 16.8 fn:static-base-uri	54
2.2	Clarifications	54
2.2.1	[XDM/2] Section 3.3.1.3, Relationship Between Typed-Value and String-Value...	55
2.2.2	[XDM/2] Section 3.3.1.4, Pattern Facets.....	55
2.2.3	[XDM/2] Section 6.2.4, Element Nodes, Construction from a PSVI	55
2.2.4	[XQuery1.0/2] Section 5.2, Optional Features	55
2.2.4.1	[XQuery1.0/2] Section 5.2.1, Schema Import Feature	55
2.2.4.2	[XQuery1.0/2] Section 5.2.2, Schema Validation Feature	55
2.2.4.3	[XQuery1.0/2] Section 5.2.3, Static Typing Feature	55
2.2.4.4	[XQuery1.0/2] Section 5.2.4, Full Axis Feature	55
2.2.4.5	[XQuery1.0/2] Section 5.2.5, Module Feature	56
2.2.4.6	[XQuery1.0/2] Section 5.2.6, Serialization Feature.....	56
2.2.5	sql:column Function.....	56
2.2.6	sql:variable Function	56
2.3	Error Handling	56
2.4	Security	56
3	Change Tracking.....	57
4	Index.....	58

1 Introduction

SQL XQuery Standards Support Document describes the level of support that is provided by Microsoft SQL Server 2008 R2 for the XQuery query language and the choices made when implementing XQuery 1.0, the XQuery 1.0 and XPath 2.0 functions and operators, and the XQuery 1.0 and XPath 2.0 data model.

XQuery is a query language that allows queries against the content of an XML document or against XML that is stored in a relational database system. The schema for the XML [maycan](#) be known or unknown. The XQuery language also allows the construction of XML output.

1.1 Glossary

This document uses the following terms:

fragment: The term "fragment" that is defined in [XDM/2].

schema collection: A collection of XML schema [XMLSCHEMA1/2] components, such as attribute, element, and type declarations, that belong to one or several target namespaces. A schema collection can be used to constrain an XML data type in SQL Server and provides type information for the nodes and values in an XML data type instance.

XML: The Extensible Markup Language, as described in [XML1.0].

XML schema: A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by XML itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[XDM/2] Berglund, A., Fernández, M., Malhotra, A., et al., Eds., "XQuery 1.0 and XPath 2.0 Data Model (XDM) (Second Edition)", W3C Recommendation, December 2010, <http://www.w3.org/TR/2010/REC-xpath-datamodel-20101214/>

[XQuery1.0/2] Boag, S., Chamberlin, D., Fernández, M., et al., Eds., "XQuery 1.0: An XML Query Language (Second Edition)", W3C Recommendation, December 2010, <http://www.w3.org/TR/2010/REC-xquery-20101214/>

[XQuery1.0XPath2.0/2] Malhotra, A., Melton, J., Walsh, N., and Kay, M., Eds., "XQuery 1.0 and XPath 2.0 Functions and Operators (Second Edition)", W3C Recommendation, December 2010, <http://www.w3.org/TR/2010/REC-xpath-functions-20101214/>

1.2.2 Informative References

[MSDN-PrimExpXQuery] Microsoft Corporation, "Primary Expressions (XQuery)", <http://msdn.microsoft.com/en-us/library/ms190754.aspx>

[MSDN-SeqTypExpXQuery] Microsoft Corporation, "SequenceType Expressions (XQuery)", <http://msdn.microsoft.com/en-us/library/ms190179.aspx>

[MSDN-XQueryLangRef] Microsoft Corporation, "XQuery Language Reference (SQL Server)", <http://msdn.microsoft.com/en-us/library/ms189075.aspx>

[XMLINFOSET] Cowan, J., and Tobin, R., Eds., "XML Information Set (Second Edition)", W3C Recommendation, February 2004, <http://www.w3.org/TR/2004/REC-xml-infoset-20040204/>

1.3 Microsoft Implementations

The standard described by this document is implemented in the product Microsoft SQL Server 2008 R2.

1.4 Standards Support Requirements

[XQuery1.0/2] section 5.1 defines minimal conformance for an XQuery processor. This conformance is defined as support for all features in the document except the following:

- Features that are called out as optional.
- Support for all functions that are listed in [XQuery1.0XPath2.0/2].
- Support for the data model [XDM/2] as defined in [XQuery1.0/2] section 5.3.

Variations from optional features are described in section 2.1 of this document. The implementation of optional features is described in section 2.2.

1.5 Notation

The following notations are used to identify clarifications in section 2.2:

Notation	Explanation
C####	This notation identifies a clarification of ambiguity in the target specification. This includes imprecise statements, omitted information, discrepancies, and errata. This does not include data formatting clarifications.
V####	This notation identifies an intended point of variability in the target specification, such as the use of MAY, SHOULD, or RECOMMENDED. This does not include extensibility points.
E####	Because the use of extensibility points (such as optional implementation-specific data) could impair interoperability, this notation identifies such points in the target specification.

2 Standards Support Statements

2.1 Normative Variations

The following subsections detail the normative variations from [XQuery1.0/2], [XQuery1.0XPath2.0/2], and [XDM/2] in XQuery in SQL Server. For complete information on the XQuery in SQL Server language, see [MSDN-XQueryLangRef].

2.1.1 Data Model Items

Section numbers that are included in the titles within the Data Model Items section refer to sections in [XDM/2].

2.1.1.1 [XDM/2] Section 1 Introduction

XQuery in SQL Server supports XML schema types with a variation. The variations are described for each type in section 2.1.3 in this document. XQuery in SQL Server supports representations of documents and of complex values. XQuery in SQL Server supports typed atomic values. XQuery in SQL Server supports ordered, heterogeneous sequences.

2.1.1.2 Concepts

2.1.1.2.1 [XDM/2] Section 2.4 Document Order

XQuery in SQL Server supports document order with a variation. XQuery in SQL Server does not support namespace nodes.

2.1.1.3 Data Model Construction

2.1.1.3.1 [XDM/2] Section 3 Data Model Construction

XQuery in SQL Server supports model instances that are based on document fragments and sequences of document nodes.

2.1.1.3.2 [XDM/2] Section 3.1 Direct Construction

2.1.1.3.3 [XDM/2] Section 3.2 Construction from an Infoset

XQuery in SQL Server supports the construction of a data model instance from an Infoset [XMLINFOSET].

2.1.1.3.4 [XDM/2] Section 3.3 Construction from a PSVI

XQuery in SQL Server supports the construction of a data model instance from a Post Schema Validation Infoset (PSVI) with a variation. XQuery in SQL Server supports the construction of a data model instance from a PSVI only with element or attribute information that is valid, or with information for which the validity is unknown. XQuery in SQL Server does not support construction of a data model from an instance with element or attribute information that is known to be invalid.

2.1.1.3.5 [XDM/2] Section 3.3.1 Mapping PSVI Additions to Node Properties

XQuery in SQL Server supports construction from a PSVI with a variation. XQuery in SQL Server supports valid nodes, and nodes whose validity is unknown. XQuery in SQL Server does not support data model construction from an instance with nodes that are known to be invalid.

2.1.1.3.6 [XDM/2] Section 3.3.1.1 Element and Attribute Node Type Names

XQuery in SQL Server supports element and attribute node type names with a variation. XQuery in SQL Server supports valid element and attribute node type names as well as element and attribute node type names whose validity is unknown. XQuery in SQL Server does not support data model construction from an instance with element and attribute node type names that are known to be invalid.

2.1.1.3.7 [XDM/2] Section 3.3.1.2 Typed Value Determination

XQuery in SQL Server supports typed value determination with a variation. XQuery in SQL Server does not support the **nilled** property.

2.1.1.3.8 [XDM/2] Section 3.3.1.3 Relationship Between Typed Value and String Value

See [XDM/2] section 3.3.1.3 for a description of items that a processor [maycan](#) optionally support.

2.1.1.3.9 [XDM/2] Section 3.3.1.4 Pattern Facets

See [XDM/2] section 3.3.1.4 for a description of items that a processor [maycan](#) optionally support.

2.1.1.3.10 [XDM/2] Section 3.3.3 QNames and NOTATIONS

XQuery in SQL Server supports QNames and NOTATIONS with a variation. XQuery in SQL Server does not support NOTATIONS.

2.1.1.4 Accessors

2.1.1.4.1 [XDM/2] Section 5 Accessors

This section of [XDM/2] describes theoretical accessors for items that exist in the data model. XQuery in SQL Server supports these accessors with a variation. XQuery in SQL Server supports the accessors for the items that are supported by XQuery in SQL Server. It does not support accessors for items that XQuery in SQL Server does not support.

Item support is described in the appropriate section for the item or type. See section 2.1.2 ["Basics"], section 2.1.3 ["Data Types"], section 2.1.4 ["Expressions"], section 2.1.5 ["Operators"], and section 2.1.6 ["Functions"]. Accessors described in this section that do not appear in the [XDM/2] are not supported by XQuery in SQL Server.

2.1.1.5 Nodes

2.1.1.5.1 [XDM/2] Section 6.2.4 Construction from a PSVI

See section 6.2.4 of [XDM/2] for a description of items that a processor [maycan](#) optionally support.

2.1.1.5.2 [XDM/2] Section 6.4 Namespace Nodes

XQuery in SQL Server does not support namespace nodes.

2.1.1.6 Conformance

2.1.1.6.1 [XDM/2] Section 7 Conformance

Section 7 Conformance of [XDM/2] states that conformance is defined by specifications that depend on the data model specification and not by the data model specification itself. The extent to which

XQuery in SQL Server conforms to the requirements that are stated in [XQuery1.0/2] and [XQuery1.0XPath2.0/2] is defined in the remainder of this document.

2.1.2 Basics

All section numbers that are included in the section names in this section correspond to the section numbers in [XQuery1.0/2]. All numbered expressions in this section correspond to numbered expressions in [XQuery1.0/2].

2.1.2.1 Expression Context

2.1.2.1.1 [XQuery1.0/2] Section 2.1.1 Static Context

Section 2.1.1 of [XQuery1.0/2] contains definitions of the individual components of the static context, but this section does not specify the normative requirements. The normative requirements are defined in appendix C.1 of [XQuery1.0/2].

2.1.2.1.1.1 [XQuery1.0/2] Appendix C.1 Static Context Components

2.1.2.1.1.1.1 XPath 1.0 Compatibility Mode

XQuery in SQL Server does not support XPath 1.0 compatibility mode.

2.1.2.1.1.1.2 Statically Known Namespaces

XQuery in SQL Server supports the statically known namespaces with a variation. By default, the local namespace is not known by XQuery in SQL Server.

2.1.2.1.1.1.3 Default Function Namespace

XQuery in SQL Server supports the default function namespace fn. XQuery in SQL Server does not support overwrite of the default function namespace in the prologue.

2.1.2.1.1.1.4 In-Scope Schema Types

The types in the xs namespace that are supported by XQuery in SQL Server are described in section 2.1.3 ["Data Types"]. XQuery in SQL Server does not support schema import in the prologue. XQuery in SQL Server does implicitly import the schema components that are contained in the XML schema collection that constrains the context-providing XML data type, if such a collection is specified.

2.1.2.1.1.1.5 In-Scope Element Declarations

XQuery in SQL Server does not support in-scope element declarations.

2.1.2.1.1.1.6 In-Scope Attribute Declarations

XQuery in SQL Server does not support in-scope attribute declarations.

2.1.2.1.1.1.7 In-Scope Variables

XQuery in SQL Server supports in-scope variables with a variation. XQuery in SQL Server does not allow specification of in-scope variables in the prologue.

2.1.2.1.1.1.8 Function Signatures

XQuery in SQL Server supports the default fn prefix for functions. For specific function support, see section 2.1.6 ["Functions"]. XQuery in SQL Server does not support augmentation of functions through schema import, module import, or through function declaration in the prologue. Constructor functions for user-defined atomic types and the **sqltypes** namespace are implicitly imported for imported XML schema collections.

2.1.2.1.1.1.9 Statically Known Collations

XQuery in SQL Server has not augmented the statically known collations with any additional collations.

2.1.2.1.1.1.10 Default Collation

XQuery in SQL Server uses the Unicode codepoint collation with a variation, as the default collation. Surrogate pairs are sorted as two characters, not one, during a collation operation.

2.1.2.1.1.1.11 Construction Mode

XQuery in SQL Server does not support the specified default construction mode. XQuery in SQL Server only supports construction mode value "strip". XQuery in SQL Server does not support setting the construction mode component in the prologue.

2.1.2.1.1.1.12 Ordering Mode

XQuery in SQL Server does not support the ordering mode value "unordered". XQuery in SQL Server supports only the ordering mode value "ordered". XQuery in SQL Server does not support specifying the ordering mode in the prologue.

2.1.2.1.1.1.13 Default Order for Empty Sequences

The implementation in XQuery in SQL Server defines the default value for the order for empty sequences as "least". XQuery in SQL Server does not support the value "greatest" for the default order for empty sequences.

2.1.2.1.1.1.14 Boundary-Space Policy

XQuery in SQL Server supports "strip" as the default value for boundary-space policy. XQuery in SQL Server does not support any other values.

2.1.2.1.1.1.15 Copy-Namespaces Mode

Copy-namespaces mode is not supported by XQuery in SQL Server.

2.1.2.1.1.1.16 Base URI

XQuery in SQL Server does not support the base URI.

2.1.2.1.1.1.17 Statically Known Documents

XQuery in SQL Server does not support statically known documents.

2.1.2.1.1.1.18 Statically Known Collections

XQuery in SQL Server does not support statically known collections.

2.1.2.1.1.1.19 Statically Known Default Collection Type

XQuery in SQL Server does not support the statically known default collection type.

2.1.2.1.2 [XQuery1.0/2] Section 2.1.2 Dynamic Context

2.1.2.1.2.1 [XQuery1.0/2] Appendix C.2 Dynamic Context Components

2.1.2.1.2.1.1 Variable Values

XQuery in SQL Server supports dynamic variable values. XQuery in SQL Server does not support variable declaration in the prologue.

2.1.2.1.2.1.2 Function Implementations

The functions supported by XQuery in SQL Server are documented in section 2.1.6 ["Functions"]. XQuery in SQL Server does not support function implementations through schema import, module import, or through function declaration in the prologue.

2.1.2.1.2.1.3 Current dateTime

Current dateTime is not supported by XQuery in SQL Server.

2.1.2.1.2.1.4 Implicit Timezone

The implicit timezone is not supported by XQuery in SQL Server.

2.1.2.1.2.1.5 Available Documents

Available documents is not supported by XQuery in SQL Server.

2.1.2.1.2.1.6 Available Collections

Available collections is not supported by XQuery in SQL Server.

2.1.2.1.2.1.7 Default Collection

Default collection is not supported by XQuery in SQL Server.

2.1.2.2 Processing Model

2.1.2.2.1 [XQuery1.0/2] Section 2.2.1 Data Model Generation

[XQuery1.0/2] section 2.2.1 specifies no normative requirements.

2.1.2.2.2 [XQuery1.0/2] Section 2.2.2 Schema Import Processing

XQuery in SQL Server supports schema import with a variation. XQuery in SQL Server does not support explicit schema import. XQuery in SQL Server implicitly imports the schemas that are included in the XML schema collection that is associated with the context-setting XML data type.

2.1.2.2.3 [XQuery1.0/2] Section 2.2.3.1 Expression Processing - Static Analysis Phase

XQuery in SQL Server supports the static analysis phase of expression processing. XQuery in SQL Server supports the static typing feature and raises the type error XPTY0004 if static analysis encounters a type error.

2.1.2.2.4 [XQuery1.0/2] Section 2.2.3.2 Expression Processing - Dynamic Evaluation Phase

XQuery in SQL Server supports a dynamic evaluation phase with a variation. XQuery in SQL Server does not raise dynamic errors. In cases where a dynamic error is encountered, XQuery in SQL Server returns an empty sequence.

2.1.2.2.5 [XQuery1.0/2] Section 2.2.4 Serialization

Data model serialization is an optional feature in [XQuery1.0/2]. XQuery in SQL Server does not support a data model serialization interface. However, XQuery in SQL Server supports serialization of an instance of an XML data type through conversion or casting to SQL string or binary types.

2.1.2.2.6 [XQuery1.0/2] Section 2.2.5 Consistency Constraints

XQuery in SQL Server supports applicable consistency constraints that relate to features supported by XQuery in SQL Server. Many of the constraints that are enumerated in section 2.2.5 of [XQuery1.0/2] are for features that are documented elsewhere in this document as not supported by XQuery in SQL Server and hence such consistency constraints are not supported.

2.1.2.3 Error Handling

2.1.2.3.1 [XQuery1.0/2] Section 2.3.1 Kinds of Errors

Raising static errors and type errors during the static analysis phase is supported by XQuery in SQL Server. Dynamic errors are not supported by XQuery in SQL Server. Dynamic errors are indicated by XQuery in SQL Server by the return of an empty sequence.

2.1.2.3.2 [XQuery1.0/2] Section 2.3.2 Identifying and Reporting Errors

[XQuery1.0/2] states that implementations can represent errors by a URI reference that is derived from the QName for the error. XQuery in SQL Server does not represent errors by a URI reference that is derived from the QName for the error.

2.1.2.3.3 [XQuery1.0/2] Section 2.3.3 Handling Dynamic Errors

XQuery in SQL Server does not report dynamic errors. When the result of the dynamic evaluation phase is an error, XQuery in SQL Server returns an empty sequence.

2.1.2.3.4 [XQuery1.0/2] Section 2.3.4 Errors and Optimization

XQuery in SQL Server performs the required cardinality check and returns an error if the cardinality check fails.

2.1.2.4 Concepts

2.1.2.4.1 [XQuery1.0/2] Section 2.4.1 Document Order

This section contains no normative requirements.

2.1.2.4.2 [XQuery1.0/2] Section 2.4.2 Atomization

This section contains no normative requirements.

2.1.2.4.3 [XQuery1.0/2] Section 2.4.3 Effective Boolean Value

XQuery in SQL Server does not support the **fn:boolean** function. XQuery in SQL Server supports the semantics of effective Boolean value in predicates and Boolean expressions with a variation. XQuery in

SQL Server returns an error if the operand is a singleton value of type **xs:string**, **xs:anyURI**, or **xs:untypedAtomic**, or a type derived that is from these types.

2.1.2.4.4 [XQuery1.0/2] Section 2.4.4 Input Sources

The **fn:doc** function is not supported by XQuery in SQL Server. The **fn:collection** function is not supported by XQuery in SQL Server. The implicit context for the query is the XML data type instance of the query.

2.1.2.4.5 [XQuery1.0/2] Section 2.4.5 URI Literals

```
[140]    URILiteral    ::=    StringLiteral
```

[140] is supported by XQuery in SQL Server. The whitespace normalization rules for URILiteral are supported by XQuery in SQL Server.

2.1.2.5 Types

2.1.2.5.1 [XQuery1.0/2] Section 2.5.1 Predefined Schema Types

This document covers the types that are supported by XQuery in SQL Server in section 2.1.3 ["Data Types"].

2.1.2.5.2 [XQuery1.0/2] Section 2.5.3 SequenceType Syntax

```
[119]    SequenceType ::=    ("empty-sequence" "(" ")")
| (ItemType OccurrenceIndicator?)
```

[119] is supported by XQuery in SQL Server.

```
[120]    OccurrenceIndicator ::=    "?" | "*" | "+"
```

[120] is supported by XQuery in SQL Server with variations. The "?" syntax is supported by XQuery in SQL Server. The "+" and "*" syntaxes are not supported by XQuery in SQL Server.

```
[121]    ItemType    ::=    KindTest | ("item" "(" ")") | AtomicType
```

[121] is supported by XQuery in SQL Server with a variation. See the information on expression [123] later in this section for limitations in KindTest.

```
[122]    AtomicType    ::=    QName
```

[122] is supported by XQuery in SQL Server.

```
[123]    KindTest    ::=    DocumentTest
| ElementTest
| AttributeTest
| SchemaElementTest
```

```
| SchemaAttributeTest
| PITest
| CommentTest
| TextTest
| AnyKindTest
```

[123] is supported by XQuery in SQL Server with a variation. The following tests are not supported by XQuery in SQL Server: DocumentTest, SchemaElementTest, SchemaAttributeTest. The following tests are supported only for type checks, but not in path expressions: ElementTest, AttributeTest.

```
[124] AnyKindTest ::= "node" "(" ")"
```

[124] is supported by XQuery in SQL Server with a variation. AnyKindTest cannot be used to access the text node of a simple typed type or of content of type **xs:anyType**.

```
[125] DocumentTest ::= "document-node" "(" (ElementTest | SchemaElementTest)? ")"
```

[125] is not supported by XQuery in SQL Server.

```
[126] TextTest ::= "text" "(" ")"
```

[126] is supported by XQuery in SQL Server with a variation. TextTest cannot be used to access the text node of a simple typed type or of content of type **xs:anyType**.

```
[127] CommentTest ::= "comment" "(" ")"
```

[127] is supported by XQuery in SQL Server.

```
[128] PITest ::= "processing-instruction" "(" (NCName | StringLiteral)? ")"
```

[128] is supported by XQuery in SQL Server.

```
[129] AttributeTest ::= "attribute" "(" (AttribNameOrWildcard ("," TypeName)?)? ")"
```

[129] is supported by XQuery in SQL Server with a variation. [129] is supported for type tests, but is not supported for path expressions.

```
[130] AttribNameOrWildcard ::= AttributeName | "**"
```

[130] is supported by XQuery in SQL Server.

```
[131] SchemaAttributeTest ::= "schema-attribute" "(" AttributeDeclaration ")"
```

[131] is not supported by XQuery in SQL Server.

```
[132] AttributeDeclaration ::= AttributeName
```

[132] is supported by XQuery in SQL Server.

```
[133] ElementTest ::= "element" "(" (ElementNameOrWildcard ("," TypeName "?"?)?)?
")"
```

[133] is supported by XQuery in SQL Server with a variation. [133] is supported in type expressions but is not supported in path expressions.

```
[134] ElementNameOrWildcard ::= ElementName | "**"
```

[134] is supported by XQuery in SQL Server.

```
[135] SchemaElementTest ::= "schema-element" "(" ElementDeclaration ")"
```

[135] is not supported by XQuery in SQL Server.

```
[136] ElementDeclaration ::= ElementName
```

[136] is supported by XQuery in SQL Server with a variation. [136] is supported in type expressions but is not supported in path expressions.

```
[137] AttributeName ::= QName
```

[137] is supported by XQuery in SQL Server.

```
[138] ElementName ::= QName
```

[138] is supported by XQuery in SQL Server.

```
[139] TypeName ::= QName
```

[139] is supported by XQuery in SQL Server. However, only the types documented in section 2.1.3 ["Data Types"] are supported.

2.1.2.5.3 [XQuery1.0/2] Section 2.5.4 SequenceType Matching

2.1.2.5.4 [XQuery1.0/2] Section 2.5.4.1 Matching a Sequence Type and a Value

Matching a sequence type and a value is supported by XQuery in SQL Server with a variation. XQuery in SQL Server supports only the "?" operator, not the "*" or the "+" operator.

2.1.2.5.5 [XQuery1.0/2] Section 2.5.4.2 Matching an Item Type and an Item

XQuery in SQL Server supports Matching an Item Type and an item with a variation. XQuery in SQL Server does not support the document(E) syntax.

2.1.2.5.6 [XQuery1.0/2] Section 2.5.4.3 Element Test

XQuery in SQL Server supports the element test with a variation. XQuery in SQL Server requires that the **Type**Name token, when specified, is followed by the "?" syntax. XQuery in SQL Server does not support the "*" syntax for specifying **Type**Name.

2.1.2.5.7 [XQuery1.0/2] Section 2.5.4.4 Schema Element Test

The schema element test is not supported by XQuery in SQL Server.

2.1.2.5.8 [XQuery1.0/2] Section 2.5.4.5 Attribute Test

XQuery in SQL Server supports the attribute test with a variation. XQuery in SQL Server requires that the **Type**Name attribute, when specified, is followed by "?". XQuery in SQL Server does not support "*" for the **Type**Name specification.

2.1.2.5.9 [XQuery1.0/2] Section 2.5.4.6 Schema Attribute Test

The schema attribute test is not supported by XQuery in SQL Server.

2.1.3 Data Types

The data types that are assessed in this document are those that appear in the figure titled "XPath 2.0 and XQUERY 1.0 Type Hierarchy" in section 2.6.3 of [XDM/2].

2.1.3.1 XSD Types

2.1.3.1.1 xs:ID

The **xs:ID** type is supported by XQuery in SQL Server with a variation. This type is supported only for attributes, not for elements.

2.1.3.1.2 xs:IDREF

The **xs:IDREF** type is supported by XQuery in SQL Server with a variation. This type is supported only for attributes, not for elements.

2.1.3.1.3 xs:untypedAtomic

The **xs:untypedAtomic** type is supported by XQuery in SQL Server with a variation. ~~The that requires the~~ type **mustto** be referenced as **xdt:untypedAtomic**.

2.1.3.1.4 xs:untyped

The **xs:untyped** type is supported by XQuery in SQL Server with a variation. ~~The that requires the~~ type **mustto** be referenced as **xdt:untyped**.

2.1.3.1.5 xs:NOTATION

The **xs:NOTATION** type is not supported by XQuery in SQL Server.

2.1.3.1.6 xs:yearMonthDuration

The **xs:yearMonthDuration** type is not supported by XQuery in SQL Server.

2.1.3.1.7 xs:dayTimeDuration

The **xs:dayTimeDuration** type is not supported by XQuery in SQL Server.

2.1.3.1.8 xs:IDREFS

The **xs:IDREFS** type is supported by XQuery in SQL Server with a variation. This type is supported only for attributes, not for elements.

2.1.3.2 Casting Primitive Type to Primitive Type

[XQuery1.0XPath2.0/2] section 17.1 has a table that describes which primitive types can be explicitly cast to other primitive types. XQuery in SQL Server supports the documented valid casts, with variations, as described in this section.

- The yearMonthDuration type and the dayTimeDuration type are not supported by XQuery in SQL Server, so no casts are valid.
- XQuery in SQL Server always supports casting between untypedAtomic and anyURI and does not restrict casting between untypedAtomic and anyURI to certain values. [XQuery1.0XPath2.0/2] specifies that casting between untypedAtomic and anyURI is restricted to certain values.
- XQuery in SQL Server always supports casting between string and anyURI, not restricted to certain values, as specified in [XQuery1.0XPath2.0/2].
- XQuery in SQL Server does not support casts from dateTime to time, date, gYearMonth, gyear, gMonthDay, gDay, and gMonth.
- XQuery in SQL Server does not support casts from date to dateTime, gYearMonth, gyear, gMonthDay, gDay, gMonth.
- XQuery in SQL Server does not support casts from QName to untypedAtomic or string.
- XQuery in SQL Server does not support casts from NOTATION to untypedAtomic, string, or NOTATION.

2.1.4 Expressions

Section numbers in this section correspond to section numbers in [XQuery1.0/2]. All numbered expressions in this section correspond to numbered expressions in [XQuery1.0/2].

2.1.4.1 Expression Syntax

2.1.4.1.1 [XQuery1.0/2] Section 3 Expressions

For [31] see [XQuery1.0/2] section 3.3.1 "Constructing Sequences".

```
[32] ExprSingle ::= FLWORExpr
| QuantifiedExpr
| TypeswitchExpr
| IfExpr
```

| OrExpr

[32] is supported by XQuery in SQL Server.

2.1.4.1.2 [XQuery1.0/2] Section 3.1 Primary Expressions

2.1.4.1.3 [XQuery1.0/2] Section 3.1.1 Literals

```
[85] Literal ::= NumericLiteral | StringLiteral
```

[85] is supported by XQuery in SQL Server.

```
[86] NumericLiteral ::= IntegerLiteral | DecimalLiteral | DoubleLiteral
```

[86] is supported by XQuery in SQL Server.

```
[141] IntegerLiteral ::= Digits
```

[141] is supported by XQuery in SQL Server.

```
[142] DecimalLiteral ::= ( "." Digits ) | ( Digits "." [0-9]* )
```

[142] is supported by XQuery in SQL Server.

```
[143] DoubleLiteral ::= ( ( "." Digits ) | ( Digits ( "." [0-9]* )? ) ) [eE] [+-]? Digits
```

[143] is supported by XQuery in SQL Server.

```
[144] StringLiteral ::= ( '"' (PredefinedEntityRef | CharRef | EscapeQuot | [^"&])* ''' ) | ( "'" (PredefinedEntityRef | CharRef | EscapeApos | [^'&])* '"' )
```

[144] is supported by XQuery in SQL Server.

```
[145] PredefinedEntityRef ::= "&" ("lt" | "gt" | "amp" | "quot" | "apos") ";"
```

[145] is supported by XQuery in SQL Server.

```
[158] Digits ::= [0-9]+
```

[158] is supported by XQuery in SQL Server.

2.1.4.1.4 [XQuery1.0/2] Section 3.1.2 Variable References

```
[87] VarRef ::= "$" VarName
```

[87] is supported by XQuery in SQL Server.

```
[88] VarName ::= QName
```

[88] is supported by XQuery in SQL Server with variance. Only local names are supported; fully qualified QNames are not supported. XQuery in SQL Server provides an extension function, the **sql:variable** function, which can be used in to refer to a QName [MSDN-PrimExpXQuery].

[XQuery1.0/2] section 3.1.2 specifies that variables **maycan** be declared in the Prolog or an imported module. XQuery in SQL Server does not support module import.

2.1.4.1.5 [XQuery1.0/2] Section 3.1.3 Parenthesized Expressions

```
[89] ParenthesizedExpr ::= "(" Expr? ")"
```

[89] is supported by XQuery in SQL Server.

2.1.4.1.6 [XQuery1.0/2] Section 3.1.4 Context Item Expression

```
[90] ContextItemExpr ::= "."
```

[90] is supported by XQuery in SQL Server.

2.1.4.1.7 [XQuery1.0/2] Section 3.1.5 Function Calls

```
[93] FunctionCall ::= QName "(" (ExprSingle ("," ExprSingle)*)? ")"
```

[93] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server returns an empty sequence for a dynamic error result instead of returning a dynamic error.

2.1.4.1.8 [XQuery1.0/2] Section 3.2 Path Expressions

```
[68] PathExpr ::= ("/" RelativePathExpr?)  
| ("//" RelativePathExpr)  
| RelativePathExpr
```

[68] is supported by XQuery in SQL Server with a variation. In the PathExpr token, a PrimaryExpression can only be used as the root of the PathExpr.

```
[69] RelativePathExpr ::= StepExpr (("/" | "//") StepExpr)*
```

[69] is supported by XQuery in SQL Server with a variation.

2.1.4.1.9 [XQuery1.0/2] Section 3.2.1 Steps


```
[70] StepExpr ::= FilterExpr | AxisStep
```

[70] is supported by XQuery in SQL Server.

```
[71] AxisStep ::= (ReverseStep | ForwardStep) PredicateList
```

[71] is supported by XQuery in SQL Server.

```
[72] ForwardStep ::= (ForwardAxis NodeTest) | AbbrevForwardStep
```

[72] is supported by XQuery in SQL Server.

```
[75] ReverseStep ::= (ReverseAxis NodeTest) | AbbrevReverseStep
```

[75] is supported by XQuery in SQL Server.

```
[82] PredicateList ::= Predicate*
```

[82] is supported by XQuery in SQL Server.

2.1.4.1.10 [XQuery1.0/2] Section 3.2.1.1 Axes

```
[73] ForwardAxis ::= ("child" "::")
| ("descendant" "::")
| ("attribute" "::")
| ("self" "::")
| ("descendant-or-self" "::")
| ("following-sibling" "::")
| ("following" "::")
```

[73] is supported by XQuery in SQL Server with variations. XQuery in SQL Server does not support the following-sibling axis, or the following axis.

```
[76] ReverseAxis ::= ("parent" "::")
| ("ancestor" "::")
| ("preceding-sibling" "::")
| ("preceding" "::")
| ("ancestor-or-self" "::")
```

[76] is supported by XQuery in SQL Server with variations. XQuery in SQL Server supports only the parent axis; it does not support the ancestor, preceding-sibling, preceding, or ancestor-or-self axes.

2.1.4.1.11 [XQuery1.0/2] Section 3.2.1.2 Node Tests

```
[78] NodeTest ::= KindTest | NameTest
```

[78] is supported by XQuery in SQL Server with a variation. Not all of the KindTests are supported. Some KindTests are not allowed in some expressions. The limitations are described in section 2.1.2.5.2 ["SequenceType Syntax"], expression [123].

```
[79] NameTest ::= QName | Wildcard
```

[79] is supported by XQuery in SQL Server.

```
[80] Wildcard ::= "*"
| (NCName ":" "**")
| ("*" ":" NCName)
```

[80] is supported by XQuery in SQL Server.

2.1.4.1.12 [XQuery1.0/2] Section 3.2.2 Predicates

XQuery in SQL Server supports predicates with a variation. XQuery in SQL Server supports only static dispatch for predicate expression evaluation.

2.1.4.1.13 [XQuery1.0/2] Section 3.2.3 Unabbreviated Syntax

Section 3.2.3 of [XQuery1.0/2] specification is not normative, and provides syntax examples. XQuery in SQL Server supports the example syntax except where it is noted in the corresponding section that XQuery in SQL Server does not support the step expression or the axis expression

2.1.4.1.14 [XQuery1.0/2] Section 3.2.4 Abbreviated Syntax

```
[74] AbbrevForwardStep ::= "@"? NodeTest
```

[74] is supported by XQuery in SQL Server.

```
[77] AbbrevReverseStep ::= ".."
```

[77] is supported by XQuery in SQL Server.

2.1.4.1.15 [XQuery1.0/2] Section 3.3.1 Constructing Sequences

```
[31] Expr ::= ExprSingle ("," ExprSingle)*
```

[31] is supported by XQuery in SQL Server with variations. XQuery in SQL Server imposes the restriction that all items in the sequence mustare required to be either nodes or atomic values⁺. Nodes and atomic values cannot be mixed.

```
[49] RangeExpr ::= AdditiveExpr ( "to" AdditiveExpr )?
```

[49] is not supported by XQuery in SQL Server.

2.1.4.1.16 [XQuery1.0/2] Section 3.3.2 Filter Expressions

```
[81] FilterExpr ::= PrimaryExpr PredicateList
```

[81] is supported by XQuery in SQL Server.

```
[82] PredicateList ::= Predicate*
```

[82] is supported by XQuery in SQL Server.

2.1.4.1.17 [XQuery1.0/2] Section 3.3.3 Combining Node Sequences

```
[52] UnionExpr ::= IntersectExceptExpr ( ("union" | "|") IntersectExceptExpr )*
```

[52] is not supported by XQuery in SQL Server.

```
[53] IntersectExceptExpr ::= InstanceofExpr ( ("intersect" | "except")  
InstanceofExpr )*
```

[53] is not supported by XQuery in SQL Server.

2.1.4.1.18 [XQuery1.0/2] Section 3.4 Arithmetic Expressions

```
[50] AdditiveExpr ::= MultiplicativeExpr ( ("+" | "-") MultiplicativeExpr )*
```

[50] is supported by XQuery in SQL Server with a variation. Operands are constrained to be of numeric type, or of type **xs:untypedAtomic**. Operations on operators of type **xs:integer** are returned as type **xs:decimal**.

```
[51] MultiplicativeExpr ::= UnionExpr ( ("*" | "div" | "idiv" | "mod") UnionExpr )*
```

[51] is supported by XQuery in SQL Server with a variation. Arguments MUST be of numeric type, or of type **xs:untypedAtomic**. Operations on operators of type **xs:integer** are returned as type **xs:decimal**. The idiv operator is not supported. A workaround is to cast a result of the div operator to **xs:integer**.

```
[58] UnaryExpr ::= ("-" | "+")* ValueExpr
```

[58] is supported by XQuery in SQL Server with a variation. Arguments are constrained to be of numeric type, or of type **xs:untypedAtomic**. Operations on operators of type **xs:integer** are returned as type **xs:decimal**.

```
[59] ValueExpr ::= ValidateExpr | PathExpr | ExtensionExpr
```

[59] is supported by XQuery in SQL Server with a variation. ValidateExpr is not supported by XQuery in SQL Server. ExtensionExpr is not supported by XQuery in SQL Server.

2.1.4.1.19 [XQuery1.0/2] Section 3.5 Comparison Expressions

```
[48] ComparisonExpr ::= RangeExpr ( (ValueComp
| GeneralComp
| NodeComp) RangeExpr )?
```

[48] is supported by XQuery in SQL Server.

2.1.4.1.20 [XQuery1.0/2] Section 3.5.1 Value Comparisons

```
[61] ValueComp ::= "eq" | "ne" | "lt" | "le" | "gt" | "ge"
```

[61] is supported by XQuery in SQL Server with variations. XQuery in SQL Server casts operands of type **xs:untypedAtomic** to the type of the other operand, not to type **xs:string**, as specified in [XQuery1.0/2].

2.1.4.1.21 [XQuery1.0/2] Section 3.5.2 General Comparisons

```
[60] GeneralComp ::= "=" | "!=" | "<" | "<=" | ">" | ">="
```

[60] is supported by XQuery in SQL Server with variations. XQuery in SQL Server casts operands of type **xs:untypedAtomic** to the type of the other operand, not to type **xs:string**, as specified in [XQuery1.0/2]. Note that expression [60] is defined in [XQuery1.0/2] section 3.5, but the description of this expression is provided in [XQuery1.0/2] section 3.5.2.

2.1.4.1.22 [XQuery1.0/2] Section 3.5.3 Node Comparisons

```
[62] NodeComp ::= "is" | "<<" | ">>"
```

[62] is supported by XQuery in SQL Server. Note that expression [63] is defined in [XQuery1.0/2] section 3.5, but the description of this expression is provided in [XQuery1.0/2] section 3.5.3.

2.1.4.1.23 [XQuery1.0/2] Section 3.6 Logical Expressions

```
[46] OrExpr ::= AndExpr ( "or" AndExpr )*
```

[46] is supported by XQuery in SQL Server with a variation in error handling.

```
[47] AndExpr ::= ComparisonExpr ( "and" ComparisonExpr )*
```

[47] is supported by XQuery in SQL Server with a variation in error handling.

Applicable to [46] and [47] is that XQuery in SQL Server maps dynamic errors to an empty sequence instead of returning a dynamic error.

2.1.4.1.24 [XQuery1.0/2] Section 3.7 Constructors

```
[94]    Constructor    ::=    DirectConstructor
      | ComputedConstructor
```

[94] is supported by XQuery in SQL Server.

```
[95]    DirectConstructor    ::=    DirElemConstructor
      | DirCommentConstructor
      | DirPIConstructor
```

[95] is supported by XQuery in SQL Server.

```
[96]    DirElemConstructor    ::=    "<" QName DirAttributeList ("/>" | (">" DirElemContent*
      "</" QName S? ">"))
```

[96] is supported by XQuery in SQL Server.

```
[101]   DirElemContent    ::=    DirectConstructor
      | CDataSection
      | CommonContent
      | ElementContentChar
```

[101] is supported by XQuery in SQL Server.

```
[148]   ElementContentChar    ::=    Char - [{}<&]
```

[148] is supported by XQuery in SQL Server.

```
[102]   CommonContent    ::=    PredefinedEntityRef | CharRef | "{{" | "}" | EnclosedExpr
```

[102] is supported by XQuery in SQL Server.

```
[107]   CDataSection    ::=    "<![CDATA[" CDataSectionContents "]">"
```

[107] is supported by XQuery in SQL Server.

```
[108]   CDataSectionContents    ::=    (Char* - (Char* ']'>' Char*))
```

[108] is supported by XQuery in SQL Server.

```
[97] DirAttributeList ::= (S (QName S? "=" S? DirAttributeValue)?)*
```

[97] is supported by XQuery in SQL Server.

```
[98] DirAttributeValue ::= ('"' (EscapeQuot | QuotAttrValueContent)* '"')  
| ("'" (EscapeApos | AposAttrValueContent)* "'")
```

[98] is supported by XQuery in SQL Server.

```
[99] QuotAttrValueContent ::= QuotAttrContentChar  
| CommonContent
```

[99] is supported by XQuery in SQL Server.

```
[100] AposAttrValueContent ::= AposAttrContentChar  
| CommonContent
```

[100] is supported by XQuery in SQL Server.

```
[149] QuotAttrContentChar ::= Char - [{"{}<&}
```

[149] is supported by XQuery in SQL Server.

```
[150] AposAttrContentChar ::= Char - [{"{}<&}
```

[150] is supported by XQuery in SQL Server.

```
[146] EscapeQuot ::= '""'
```

[146] is supported by XQuery in SQL Server.

```
[147] EscapeApos ::= ""''"
```

[147] is supported by XQuery in SQL Server.

```
[29] EnclosedExpr ::= "{" Expr "}"
```

[29] is supported by XQuery in SQL Server.

2.1.4.1.25 [XQuery1.0/2] Section 3.7.1 Direct Element Constructors

XQuery in SQL Server supports direct element constructors with a variation. XQuery in SQL Server does not support the base-URI mechanism for specifying a reference as a relative URI.

2.1.4.1.26 [XQuery1.0/2] Section 3.7.1.1 Attributes

XQuery in SQL Server supports direct attribute constructors with a variation. XQuery in SQL Server does not support multiple or mixed embedded attribute expressions. The expression MUST be either a single string or a single expression. XQuery in SQL Server requires homogeneous sequences. Castability is checked statically and atomization is not applied before the check.

2.1.4.1.27 [XQuery1.0/2] Section 3.7.1.2 Namespace Declaration Attributes

Namespace declaration attributes are supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not check the validity of any provided string against the type **xs:anyURI**.

2.1.4.1.28 [XQuery1.0/2] Section 3.7.1.3 Content

XQuery in SQL Server supports constructors for content with a variation. The specification [XQuery1.0/2] specifies that if nodes within expressions cannot be cast to type **xs:string**, an error is generated. XQuery in SQL Server evaluates types statically instead of attempting to cast to string and generates a static error if the static types do not enable string output.

XQuery in SQL Server does not support the **base-uri** property for nodes created by expressions. XQuery in SQL Server supports only construction mode value "strip", and so statements in [XQuery1.0/2] that describe any other construction modes are not applicable.

XQuery in SQL Server does not support the concept of in-scope namespaces. A recommendation to work around this is to always make all namespaces explicit. [XQuery1.0/2] specifies that if an attribute node follows other nodes, a type error is raised. XQuery in SQL Server raises a dynamic error if an attribute node follows other nodes.

2.1.4.1.29 [XQuery1.0/2] Section 3.7.1.4 Boundary Whitespace

XQuery in SQL Server supports only one boundary whitespace policy, "strip".

2.1.4.1.30 [XQuery1.0/2] Section 3.7.2 Other Direct Constructors

```
[105] DirPIConstructor ::= "<?" PITarget (S DirPIContents)? ">"
```

[105] is supported by XQuery in SQL Server.

```
[106] DirPIContents ::= (Char* - (Char* '?>' Char*))
```

[106] is supported by XQuery in SQL Server.

```
[103] DirCommentConstructor ::= "<!--" DirCommentContents "-->"
```

[103] is supported by XQuery in SQL Server.

```
[104] DirCommentContents ::= ((Char - '-') | ('-' (Char - '-')))*
```

[104] is supported by XQuery in SQL Server.

2.1.4.1.31 [XQuery1.0/2] Section 3.7.3 Computed Constructors

```
[109] ComputedConstructor ::= CompDocConstructor
| CompElemConstructor
| CompAttrConstructor
| CompTextConstructor
| CompCommentConstructor
| CompPIConstructor
```

[109] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not support `CompDocConstructor`, `CompCommentConstructor`, or `CompPIConstructor`. XQuery in SQL Server does not support expressions in the definition of the name for computed element or computed attribute constructors.

2.1.4.1.32 [XQuery1.0/2] Section 3.7.3.1 Computed Element Constructors

```
[111] CompElemConstructor ::= "element" (QName | (" Expr ")) "{" ContentExpr?
}"
```

[111] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server supports only `QName` and does not support `Expr` for the name of the computed element.

```
[112] ContentExpr ::= Expr
```

[112] is supported by XQuery in SQL Server.

2.1.4.1.33 [XQuery1.0/2] Section 3.7.3.2 Computed Attribute Constructors

```
[113] CompAttrConstructor ::= "attribute" (QName | (" Expr ")) "{" Expr? "
```

[113] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not support expressions for the name of the computed attribute.

2.1.4.1.34 [XQuery1.0/2] Section 3.7.3.3 Document Node Constructors

```
[110] CompDocConstructor ::= "document" "{" Expr "
```

[110] is not supported by XQuery in SQL Server. However, all query method results are implicitly wrapped in a document node.

2.1.4.1.35 [XQuery1.0/2] Section 3.7.3.4 Text Node Constructors

```
[114] CompTextConstructor ::= "text" "{" Expr "
```

[114] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server supports only `ExprSingle` and not `Expr`.

2.1.4.1.36 [XQuery1.0/2] Section 3.7.3.5 Computed Processing Instruction Constructors

```
[116]   CompPIConstructor   ::=   "processing-instruction" (NCName | ("{" Expr "}")) "{"  
Expr? "}"
```

[116] is not supported by XQuery in SQL Server. The direct processing instruction (PI) constructor can be used as an alternative.

2.1.4.1.37 [XQuery1.0/2] Section 3.7.3.6 Computed Comment Constructors

```
[115]   CompCommentConstructor   ::=   "comment" "{" Expr "}"
```

[115] is not supported by XQuery in SQL Server. The direct comment constructor can be used as an alternative.

2.1.4.1.38 [XQuery1.0/2] Section 3.7.4 In-scope Namespaces of a Constructed Element

XQuery in SQL Server supports the In-scope Namespaces of a Constructed Element rules with a variation. XQuery in SQL Server does not carry over namespaces that have been declared but which are not actually used in the constructor.

2.1.4.1.39 [XQuery1.0/2] Section 3.8 FLWOR Expressions

```
[33]   FLWORExpr           ::=   (ForClause | LetClause)+ WhereClause? OrderByClause? "return"  
ExprSingle
```

[33] is supported by XQuery in SQL Server.

```
[34]   ForClause           ::=   "for" "$" VarName TypeDeclaration? PositionalVar? "in" ExprSingle  
(", " "$" VarName TypeDeclaration? PositionalVar? "in" ExprSingle)*
```

[34] is supported by XQuery in SQL Server with a variation. TypeDeclaration is not supported by XQuery in SQL Server. PositionalVar is not supported by XQuery in SQL Server.

```
[36]   LetClause           ::=   "let" "$" VarName TypeDeclaration? ":" ExprSingle ("," "$"  
VarName TypeDeclaration? ":" ExprSingle)*
```

[36] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not support TypeDeclaration in the Let clause.

```
[118]   TypeDeclaration     ::=   "as" SequenceType
```

[118] is not supported by XQuery in SQL Server.

```
[35] PositionalVar ::= "at" "$" VarName
```

[35] is not supported by XQuery in SQL Server.

```
[37] WhereClause ::= "where" ExprSingle
```

[37] is supported by XQuery in SQL Server.

```
[38] OrderByClause ::= (("order" "by") | ("stable" "order" "by")) OrderSpecList
```

[38] is supported by XQuery in SQL Server with a variation. The syntax "stable order by" is not supported. However, the order obtained with the syntax "order by" results in a stable order by default.

```
[39] OrderSpecList ::= OrderSpec ("," OrderSpec)*
```

[39] is supported by XQuery in SQL Server.

```
[40] OrderSpec ::= ExprSingle OrderModifier
```

[40] is supported by XQuery in SQL Server.

```
[41] OrderModifier ::= ("ascending" | "descending")? ("empty" ("greatest" | "least"))? ("collation" URILiteral)?
```

[41] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not offer an option to declare empty as greatest or least, and empty is treated as least by default. XQuery in SQL Server does not support collation.

2.1.4.1.40 [XQuery1.0/2] Section 3.8.1 For and Let Clauses

For and Let clauses are supported by XQuery in SQL Server. See section 2.1.4.1.39 ["3.8 FLWOR Expressions"], items [34] and [36].

2.1.4.1.41 [XQuery1.0/2] Section 3.8.2 Where Clause

The Where clause is supported by XQuery in SQL Server. See section 2.1.4.1.39 ["3.8 FLWOR Expressions"], item [37].

2.1.4.1.42 [XQuery1.0/2] Section 3.8.3 Order By and Return Clauses

Order By and Return clauses are supported by XQuery in SQL Server. See section 2.1.4.1.39 ["3.8 FLWOR Expressions"], item [38].

2.1.4.1.43 [XQuery1.0/2] Section 3.9 Ordered and Unordered Expressions

```
[91] OrderedExpr ::= "ordered" "{" Expr "}"
```

[91] is not supported by XQuery in SQL Server. All expressions are evaluated as ordered.

```
[92] UnorderedExpr ::= "unordered" "(" Expr ")"
```

[92] is not supported by XQuery in SQL Server. All expressions are evaluated as ordered.

2.1.4.1.44 [XQuery1.0/2] Section 3.10 Conditional Expressions

```
[45] IfExpr ::= "if" "(" Expr ")" "then" ExprSingle "else" ExprSingle
```

[45] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server permits only ExprSingle in the condition.

2.1.4.1.45 [XQuery1.0/2] Section 3.11 Quantified Expressions

```
[42] QuantifiedExpr ::= ("some" | "every") "$" VarName TypeDeclaration? "in" ExprSingle ("," "$" VarName TypeDeclaration? "in" ExprSingle)* "satisfies" ExprSingle
```

[42] is supported by XQuery in SQL Server with a variation.

```
[118] TypeDeclaration ::= "as" SequenceType
```

[118] is not supported by XQuery in SQL Server.

2.1.4.1.46 [XQuery1.0/2] Section 3.12.1 Instance Of

```
[54] InstanceofExpr ::= TreatExpr ( "instance" "of" SequenceType )?
```

[54] is supported by XQuery in SQL Server with a variation. The only occurrence indicator for the SequenceType that is supported is the "?" character. The "+" and the "*" occurrence indicators are not supported. The schema-element() and schema-attribute() sequence types are not supported.

XQuery in SQL Server does not support detection of **xs:nil** at run time. (This functionality can be obtained by using the "?" occurrence indicator, as for example xs:string?). For union types, the primitive type, not the derived type, is returned. For the **processing-instruction()** and **document-node()** types, only the form with 0 arguments are allowed by XQuery in SQL Server.

For more information see [MSDN-SeqTypExpXQuery]. For further information on the support for SequenceType, see section 2.1.2.5.3 ["SequenceType Matching"].

2.1.4.1.47 [XQuery1.0/2] Section 3.12.2 Typeswitch

```
[43] TypeswitchExpr ::= "typeswitch" "(" Expr ")" CaseClause+ "default" (" $" VarName)? "return" ExprSingle
```

[43] is not supported by XQuery in SQL Server.

```
[44] CaseClause ::= "case" ("$" VarName "as")? SequenceType "return" ExprSingle
```

[44] is not supported by XQuery in SQL Server.

2.1.4.1.48 [XQuery1.0/2] Section 3.12.3 Cast

```
[57] CastExpr ::= UnaryExpr ( "cast" "as" SingleType )?
```

[57] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server requires that the syntax contain the cardinality indicator, the "?" character, to be part of the SingleType expression.

```
[117] SingleType ::= AtomicType "?"?
```

[117] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server requires the "?" cardinality indicator to be present after the AtomicType.

2.1.4.1.49 [XQuery1.0/2] Section 3.12.4 Castable

```
[56] CastableExpr ::= CastExpr ( "castable" "as" SingleType )?
```

[56] is not supported by XQuery in SQL Server.

```
[117] SingleType ::= AtomicType "?"?
```

[117] is not supported by XQuery in SQL Server.

2.1.4.1.50 [XQuery1.0/2] Section 3.12.5 Constructor Functions

XQuery in SQL Server supports the constructor functions. This syntax is an alternate syntax for casting. Any limitations noted in section 2.1.4.1.48 ["Cast"] apply to the constructor functions as well.

2.1.4.1.51 [XQuery1.0/2] Section 3.12.6 Treat

```
[55] TreatExpr ::= CastableExpr ( "treat" "as" SequenceType )?
```

[55] is not supported by XQuery in SQL Server.

2.1.4.1.52 [XQuery1.0/2] Section 3.13 Validate Expressions

```
[63] ValidateExpr ::= "validate" ValidationMode? "{" Expr "}"
```

[63] is not supported by XQuery in SQL Server.

```
[64] ValidationMode ::= "lax" | "strict"
```

[64] is not supported by XQuery in SQL Server.

2.1.4.1.53 [XQuery1.0/2] Section 3.14 Extension Expressions

Extension expressions are not supported by XQuery in SQL Server.

2.1.4.1.54 [XQuery1.0/2] Appendix A.1 EBNF

Appendix A.1 contains additional normative expressions that do not appear in other sections of [XQuery1.0/2]. Expressions not covered elsewhere are included in this section.

```
[65] ExtensionExpr ::= Pragma+ "{" Expr? "}"
```

[65] is not supported by XQuery in SQL Server.

```
[66] Pragma ::= "(# S? QName (S PragmaContents)? "#)"
```

[66] is not supported by XQuery in SQL Server.

```
[67] PragmaContents ::= (Char* - (Char* '#' Char*))
```

[67] is not supported by XQuery in SQL Server.

```
[83] Predicate ::= "[" Expr "]"
```

[83] is supported by XQuery in SQL Server.

```
[84] PrimaryExpr ::= Literal | VarRef | ParenthesizedExpr | ContextItemExpr |  
FunctionCall | OrderedExpr | UnorderedExpr | Constructor
```

[84] is supported by XQuery in SQL Server.

2.1.4.2 Modules and Prologs

2.1.4.2.1 [XQuery1.0/2] Section 4 Modules and Prologs

```
[1] Module ::= VersionDecl? (LibraryModule | MainModule)
```

[1] is not supported by XQuery in SQL Server.

```
[3] MainModule ::= Prolog QueryBody
```

[3] is supported by XQuery in SQL Server.

```
[4] LibraryModule ::= ModuleDecl Prolog
```

[4] is not supported by XQuery in SQL Server.

```
[6] Prolog ::= ((DefaultNamespaceDecl | Setter | NamespaceDecl | Import) Separator)*  
((VarDecl | FunctionDecl | OptionDecl) Separator)*
```

[6] is supported by XQuery in SQL Server with a variation. Some of the declarations listed are not supported. See the expression for each token in this document for the description of its support.

```
[7] Setter ::= BoundarySpaceDecl | DefaultCollationDecl | BaseURIDecl |  
ConstructionDecl | OrderingModeDecl | EmptyOrderDecl | CopyNamespacesDecl
```

[7] is not supported by XQuery in SQL Server.

```
[8] Import ::= SchemaImport | ModuleImport
```

[8] is not supported by XQuery in SQL Server.

```
[9] Separator ::= ","
```

[9] is supported by XQuery in SQL Server.

```
[30] QueryBody ::= Expr
```

[30] is supported by XQuery in SQL Server.

2.1.4.2.2 [XQuery1.0/2] Section 4.1 Version Declaration

```
[2] VersionDecl ::= "xquery" "version" StringLiteral ("encoding" StringLiteral)?  
Separator
```

[2] is not supported by XQuery in SQL Server.

2.1.4.2.3 [XQuery1.0/2] Section 4.2 Module Declaration

```
[5] ModuleDecl ::= "module" "namespace" NCName "=" URILiteral Separator
```

[5] is not supported by XQuery in SQL Server.

2.1.4.2.4 [XQuery1.0/2] Section 4.3 Boundary-space Declaration

```
[11] BoundarySpaceDecl ::= "declare" "boundary-space" ("preserve" | "strip")
```

[11] is not supported by XQuery in SQL Server.

2.1.4.2.5 [XQuery1.0/2] Section 4.4 Default Collation Declaration

```
[19] DefaultCollationDecl ::= "declare" "default" "collation" URILiteral
```

[19] is not supported by XQuery in SQL Server.

2.1.4.2.6 [XQuery1.0/2] Section 4.5 Base URI Declaration

```
[20] BaseURIDecl ::= "declare" "base-uri" URILiteral
```

[20] is not supported by XQuery in SQL Server.

2.1.4.2.7 [XQuery1.0/2] Section 4.6 Construction Declaration

```
[25] ConstructionDecl ::= "declare" "construction" ("strip" | "preserve")
```

[25] is not supported by XQuery in SQL Server.

2.1.4.2.8 [XQuery1.0/2] Section 4.7 Ordering Mode Declaration

```
[14] OrderingModeDecl ::= "declare" "ordering" ("ordered" | "unordered")
```

[14] is not supported by XQuery in SQL Server.

2.1.4.2.9 [XQuery1.0/2] Section 4.8 Empty Order Declaration

```
[15] EmptyOrderDecl ::= "declare" "default" "order" "empty" ("greatest" | "least")
```

[15] is not supported by XQuery in SQL Server.

2.1.4.2.10 [XQuery1.0/2] Section 4.9 Copy-Namespaces Declaration

```
[16] CopyNamespacesDecl ::= "declare" "copy-namespaces" PreserveMode "," InheritMode
```

[16] is not supported by XQuery in SQL Server.

```
[17] PreserveMode ::= "preserve" | "no-preserve"
```

[17] is not supported by XQuery in SQL Server.

```
[18] InheritMode ::= "inherit" | "no-inherit"
```

[18] is not supported by XQuery in SQL Server.

2.1.4.2.11 [XQuery1.0/2] Section 4.10 Schema Import

```
[21] SchemaImport ::= "import" "schema" SchemaPrefix? URILiteral ("at" URILiteral  
(", " URILiteral)*)?
```

[21] is not supported by XQuery in SQL Server. XQuery in SQL Server implicitly imports schema information from a schema collection that can be associated with an XML data type.

```
[22] SchemaPrefix ::= ("namespace" NCName "=") | ("default" "element" "namespace")
```

[22] is not supported by XQuery in SQL Server.

2.1.4.2.12 [XQuery1.0/2] Section 4.11 Module Import

```
[23] ModuleImport ::= "import" "module" ("namespace" NCName "=")? URILiteral ("at"  
URILiteral ("," URILiteral)*)?
```

[23] is not supported by XQuery in SQL Server.

2.1.4.2.13 [XQuery1.0/2] Section 4.12 Namespace Declaration

```
[10] NamespaceDecl ::= "declare" "namespace" NCName "=" URILiteral
```

[10] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not check for the validity of the provided URI.

2.1.4.2.14 [XQuery1.0/2] Section 4.13 Default Namespace Declaration

```
[12] DefaultNamespaceDecl ::= "declare" "default" ("element" | "function")  
"namespace" URILiteral
```

[12] is supported by XQuery in SQL Server with a variation. XQuery in SQL Server does not support declaration of a default namespace for functions. XQuery in SQL Server does not support the use of a zero-length string to undefine a namespace.

2.1.4.2.15 [XQuery1.0/2] Section 4.14 Variable Declaration

```
[24] VarDecl ::= "declare" "variable" "$" QName TypeDeclaration? ((":=" ExprSingle)  
| "external")
```

[24] is not supported by XQuery in SQL Server.


```
[88] VarName ::= QName
```

[88] is not supported by XQuery in SQL Server.

```
[118] TypeDeclaration ::= "as" SequenceType
```

[118] is not supported by XQuery in SQL Server.

2.1.4.2.16 [XQuery1.0/2] Section 4.15 Function Declaration

```
[26] FunctionDecl ::= "declare" "function" QName "(" ParamList? ")" ("as" SequenceType)? (EnclosedExpr | "external")
```

[26] is not supported by XQuery in SQL Server.

```
[27] ParamList ::= Param ("," Param)*
```

[27] is not supported by XQuery in SQL Server.

```
[28] Param ::= "$" QName TypeDeclaration?
```

[28] is not supported by XQuery in SQL Server.

```
[118] TypeDeclaration ::= "as" SequenceType
```

[118] is not supported by XQuery in SQL Server.

2.1.4.2.17 [XQuery1.0/2] Section 4.16 Option Declaration

```
[13] OptionDecl ::= "declare" "option" QName StringLiteral
```

[13] is not supported by XQuery in SQL Server.

2.1.5 Operators

The operators and sections referred to in this section are found in [XQuery1.0XPath2.0/2].

2.1.5.1 Numeric Operators

XQuery in SQL Server does not support the infinite value NaN. XQuery in SQL Server returns an empty sequence when NaN is specified.

2.1.5.1.1 [XQuery1.0XPath2.0/2] Section 6.2.4 op:numeric-divide

XQuery in SQL Server supports the division operation with the "/" operator.

2.1.5.1.2 [XQuery1.0XPath2.0/2] Section 6.2.5 op:numeric-integer-divide

XQuery in SQL Server does not support an integer-division operator. Casting can be used to obtain a result similar to an integer divide operation.

2.1.5.2 String Operators

The standard [XQuery1.0XPath2.0/2] does not specify any string operators.

2.1.5.3 anyURI Operators

The standard [XQuery1.0XPath2.0/2] does not specify any operators for anyURI.

2.1.5.4 Boolean Operators

2.1.5.4.1 [XQuery1.0XPath2.0/2] Section 9.2.2 op:boolean-less-than

XQuery in SQL Server supports Boolean less-than operations with the "lt" and "ge" operators.

2.1.5.4.2 [XQuery1.0XPath2.0/2] Section 9.2.3 op:boolean-greater-than

XQuery in SQL Server supports Boolean greater-than operations with the "gt" and "le" operators.

2.1.5.5 Durations, Dates, and Times Operators

2.1.5.5.1 [XQuery1.0XPath2.0/2] Section 10.4.1 op:yearMonthDuration-less-than

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.2 [XQuery1.0XPath2.0/2] Section 10.4.2 op:yearMonthDuration-greater-than

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.3 [XQuery1.0XPath2.0/2] Section 10.4.3 op:dayTimeDuration-less-than

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.4 [XQuery1.0XPath2.0/2] Section 10.4.4 op:dayTimeDuration-greater-than

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.5 [XQuery1.0XPath2.0/2] Section 10.4.6 op:dateTime-equal

XQuery in SQL Server supports the dateTime-equal operation on values of type **xs:dateTime** with the "eq" and the "ne" operators.

2.1.5.5.6 [XQuery1.0XPath2.0/2] Section 10.4.8 op:dateTime-greater-than

XQuery in SQL Server supports the dateTime greater-than operation on values of type **xs:dateTime** with the "gt" and the "ge" operators.

2.1.5.5.7 [XQuery1.0XPath2.0/2] Section 10.4.9 op:date-equal

XQuery in SQL Server supports the date equal operation on values of type **xs:date** with the "eq" and the "ne" operators.

2.1.5.5.8 [XQuery1.0XPath2.0/2] Section 10.4.10 op:date-less-than

XQuery in SQL Server supports the date less-than operation on values of type **xs:date** with the "lt" and the "le" operators.

2.1.5.5.9 [XQuery1.0XPath2.0/2] Section 10.4.12 op:time-equal

XQuery in SQL Server supports the equality operation on values of type **xs:time** with the "eq" and the "ne" operators.

2.1.5.5.10 [XQuery1.0XPath2.0/2] Section 10.6.1 op:add-yearMonthDurations

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.11 [XQuery1.0XPath2.0/2] Section 10.6.2 op:subtract-yearMonthDurations

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.12 [XQuery1.0XPath2.0/2] Section 10.6.3 op:multiply-yearMonthDuration

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.13 [XQuery1.0XPath2.0/2] Section 10.6.4 op:divide-yearMonthDuration

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.14 [XQuery1.0XPath2.0/2] Section 10.6.5 op:divide-yearMonthDuration-by-yearMonthDuration

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.15 [XQuery1.0XPath2.0/2] Section 10.6.6 op:add-dayTimeDurations

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.16 [XQuery1.0XPath2.0/2] Section 10.6.7 op:subtract-dayTimeDurations

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.17 [XQuery1.0XPath2.0/2] Section 10.6.8 op:multiply-dayTimeDuration

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.18 [XQuery1.0XPath2.0/2] Section 10.6.9 op:divide-dayTimeDuration

As XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.19 [XQuery1.0XPath2.0/2] Section 10.6.10 op:divide-dayTimeDuration-by-dayTimeDuration

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.20 [XQuery1.0XPath2.0/2] Section 10.8.4 op:add-yearMonthDuration-to-dateTime

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.21 [XQuery1.0XPath2.0/2] Section 10.8.5 op:add-dayTimeDuration-to-dateTime

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.22 [XQuery1.0XPath2.0/2] Section 10.8.6 op:subtract-yearMonthDuration-from-dateTime

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.23 [XQuery1.0XPath2.0/2] Section 10.8.7 op:subtract-dayTimeDuration-from-dateTime

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.24 [XQuery1.0XPath2.0/2] Section 10.8.8 op:add-yearMonthDuration-to-date

As XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.25 [XQuery1.0XPath2.0/2] Section 10.8.9 op:add-dayTimeDuration-to-date

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.26 [XQuery1.0XPath2.0/2] Section 10.8.10 op:subtract-yearMonthDuration-from-date

Because XQuery in SQL Server does not support type **xs:yearMonthDuration** (see section 2.1.3.1.6 [xs:yearMonthDuration]), no operators are supported for this type.

2.1.5.5.27 [XQuery1.0XPath2.0/2] Section 10.8.11 op:subtract-dayTimeDuration-from-date

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.28 [XQuery1.0XPath2.0/2] Section 10.8.12 op:add-dayTimeDuration-to-time

Because XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.5.29 [XQuery1.0XPath2.0/2] Section 10.8.13 op:subtract-dayTimeDuration-from-time

As XQuery in SQL Server does not support type **xs:dayTimeDuration** (see section 2.1.3.1.7 [xs:dayTimeDuration]), no operators are supported for this type.

2.1.5.6 Notation Operators

2.1.5.6.1 [XQuery1.0XPath2.0/2] Section 13.1.1 op:NOTATION-equal

Because XQuery in SQL Server does not support type **xs:NOTATION** (see section 2.1.3.1.5 [xs:NOTATION]), no operators are supported for this type.

2.1.5.7 Sequences Operators

2.1.5.7.1 [XQuery1.0XPath2.0/2] Section 15.3.2 op:union

Because XQuery in SQL Server does not support a union operation (see section 2.1.4.1.17 ["Section 3.3.3 combining node sequences"]) expression [52], no operators are supported for this operation.

2.1.5.7.2 [XQuery1.0XPath2.0/2] Section 15.3.3 op:intersect

Because XQuery in SQL Server does not support an intersect operation (see section 2.1.4.1.17 ["Section 3.3.3 combining node sequences"]) expression [53], no operators are supported for this operation.

2.1.5.7.3 [XQuery1.0XPath2.0/2] Section 15.3.4 op:except

Because XQuery in SQL Server does not support an except operation (see section 2.1.4.1.17 ["Section 3.3.3 combining node sequences"]), no operators are supported for this operation.

2.1.5.7.4 [XQuery1.0XPath2.0/2] Section 15.5.1 op:to

Because XQuery in SQL Server does not support a sequence generation operation (see section 2.1.4.1.17 ["Section 3.3.3 combining node sequences"]) expression [49], no operators are supported for this operation.

2.1.5.8 Context

The standard [XQuery1.0XPath2.0/2] does not specify any operators for Context.

2.1.6 Functions

The functions and sections referred to in this section are found in [XQuery1.0XPath2.0/2].

2.1.6.1 Accessors

2.1.6.1.1 [XQuery1.0XPath2.0/2] Section 2.1 fn:node-name

The **fn:node-name** function is not supported by XQuery in SQL Server.

2.1.6.1.2 [XQuery1.0XPath2.0/2] Section 2.2 fn:nilled

The **fn:nilled** function is not supported by XQuery in SQL Server.

2.1.6.1.3 [XQuery1.0XPath2.0/2] Section 2.3 fn:string

The **fn:string** function is supported with a variation by XQuery in SQL Server. **fn:string()** (with no arguments) can be used only within a context-dependent predicate.

2.1.6.1.4 [XQuery1.0XPath2.0/2] Section 2.5 fn:base-uri

The **fn:base-uri** function is not supported by XQuery in SQL Server.

2.1.6.1.5 [XQuery1.0XPath2.0/2] Section 2.6 fn:document-uri

The **fn:document-uri** function is not supported by XQuery in SQL Server.

2.1.6.2 Numeric Functions

2.1.6.2.1 [XQuery1.0XPath2.0/2] Section 6.4.1 fn:abs

The **fn:abs** function is not supported by XQuery in SQL Server.

2.1.6.2.2 [XQuery1.0XPath2.0/2] Section 6.4.2 fn:ceiling

The **fn:ceiling** function is supported by XQuery in SQL Server with variations. The standard [XQuery1.0XPath2.0/2] requires that four types of arguments be returned as the same type as the argument: these are **xs:float**, **xs:double**, **xs:decimal**, **xs:integer**. XQuery in SQL Server returns three of those types as the same type as the argument: **xs:float**, **xs:double**, **xs:decimal**.

In XQuery in SQL Server, if the input is **xdt:untypedAtomic**, it is cast to **xs:double**. All other numeric types are returned as the base type from which they are derived.

2.1.6.2.3 [XQuery1.0XPath2.0/2] Section 6.4.3 fn:floor

The **fn:floor** function is supported by XQuery in SQL Server with variations. The standard [XQuery1.0XPath2.0/2] requires that four types of arguments be returned as the same type as the argument: these are **xs:float**, **xs:double**, **xs:decimal**, **xs:integer**. XQuery in SQL Server returns three of those types as the same type as the argument: **xs:float**, **xs:double**, **xs:decimal**.

In XQuery in SQL Server, if the input is **xdt:untypedAtomic**, it is cast to **xs:double**. All other numeric types are returned as the base type from which they are derived.

2.1.6.2.4 [XQuery1.0XPath2.0/2] Section 6.4.4 fn:round

The **fn:round** function is supported by XQuery in SQL Server with variations. The standard [XQuery1.0XPath2.0/2] requires that four types of arguments be returned as the same type as the argument: these are **xs:float**, **xs:double**, **xs:decimal**, **xs:integer**. XQuery in SQL Server returns three of those types as the same type as the argument: **xs:float**, **xs:double**, **xs:decimal**.

In XQuery in SQL Server, if the input is **xdt:untypedAtomic**, it is cast to **xs:double**. All other numeric types are returned as the base type from which they are derived. If the argument is between -0.5 and 0, XQuery in SQL Server returns the value 0, instead of the value -0, which is specified in [XQuery1.0XPath2.0/2].

2.1.6.2.5 [XQuery1.0XPath2.0/2] Section 6.4.5 fn:round-half-to-even

The **fn:round-half-to-even** function is not supported by XQuery in SQL Server.

2.1.6.3 String Functions

2.1.6.3.1 [XQuery1.0XPath2.0/2] Section 7.2.1 fn:codepoints-to-string

The **fn:codepoints-to-string** function is not supported by XQuery in SQL Server.

2.1.6.3.2 [XQuery1.0XPath2.0/2] Section 7.2.2 fn:string-to-codepoints

The **fn:string-to-codepoints** function is not supported by XQuery in SQL Server.

2.1.6.3.3 [XQuery1.0XPath2.0/2] Section 7.3.2 fn:compare

The **fn:compare** function is not supported by XQuery in SQL Server.

2.1.6.3.4 [XQuery1.0XPath2.0/2] Section 7.3.3 fn:codepoint-equal

The **fn:codepoints-equal** function is not supported by XQuery in SQL Server.

2.1.6.3.5 [XQuery1.0XPath2.0/2] Section 7.4.1 fn:concat

The **fn:concat** function is supported by XQuery in SQL Server with a variation. [XQuery1.0XPath2.0/2] specifies that the arguments are of type **anyAtomicType**, but XQuery in SQL Server specifies that arguments be of type **xs:string** or a type that is derived from **xs:string**.

2.1.6.3.6 [XQuery1.0XPath2.0/2] Section 7.4.2 fn:string-join

The **fn:string-join** function is not supported by XQuery in SQL Server.

2.1.6.3.7 [XQuery1.0XPath2.0/2] Section 7.4.3 fn:substring

The **fn:substring** function is supported by XQuery in SQL Server with a variation. The W3C specification [XQuery1.0XPath2.0/2] specifies that the second argument, *\$startingLoc*, and the third argument, *\$length*, are of type **xs:double**, but XQuery in SQL Server specifies arguments of type **xs:decimal**. The **fn:substring** function in XQuery in SQL Server version SQL Server 2008 R2 counts surrogate pairs as two characters, not one. Starting with XQuery in Microsoft SQL Server 2012, surrogate pairs are counted as only one character].

2.1.6.3.8 [XQuery1.0XPath2.0/2] Section 7.4.4 fn:string-length

The **fn:string-length** function is supported by XQuery in SQL Server with a variation. XQuery in SQL Server supports only the form string-length() (with no specified arguments) within a context dependent predicate. The **fn:string-length** function in XQuery in SQL Server version SQL Server 2008 R2 counts surrogate pairs as two characters, not one. Starting with XQuery in SQL Server 2012, this has been corrected and surrogate pairs are only counted as one character.

2.1.6.3.9 [XQuery1.0XPath2.0/2] Section 7.4.5 fn:normalize-space

The **fn:normalize-space** function is not supported by XQuery in SQL Server.

2.1.6.3.10 [XQuery1.0XPath2.0/2] Section 7.4.6 fn:normalize-unicode

The **fn:normalize-unicode** function is not supported by XQuery in SQL Server.

2.1.6.3.11 [XQuery1.0XPath2.0/2] Section 7.4.9 fn:translate

The **fn:translate** function is not supported by XQuery in SQL Server.

2.1.6.3.12 [XQuery1.0XPath2.0/2] Section 7.4.10 fn:encode-for-uri

The **fn:encode-for-uri** function is not supported by XQuery in SQL Server.

2.1.6.3.13 [XQuery1.0XPath2.0/2] Section 7.4.11 fn:iri-to-uri

The **fn:encode-for-uri** function is not supported by XQuery in SQL Server.

2.1.6.3.14 [XQuery1.0XPath2.0/2] Section 7.4.12 fn:escape-html-uri

The **fn:escape-html-uri** function is not supported by XQuery in SQL Server.

2.1.6.3.15 [XQuery1.0XPath2.0/2] Section 7.5.1 fn:contains

The **fn:contains** function is supported by XQuery in SQL Server with a variation. [XQuery1.0XPath2.0/2] specifies three arguments for the **fn:contains** function. XQuery in SQL Server supports only the first two arguments, and does not allow inclusion of the third argument, *\$collation*. XQuery in SQL Server requires ~~that~~ the string that is specified as *\$arg2* ~~must~~ be less than or equal to 4000 characters in length.

2.1.6.3.16 [XQuery1.0XPath2.0/2] Section 7.5.2 fn:starts-with

The **fn:starts-with** function is not supported by XQuery in SQL Server.

2.1.6.3.17 [XQuery1.0XPath2.0/2] Section 7.5.3 fn:ends-with

The **fn:ends-with** function is not supported by XQuery in SQL Server.

2.1.6.3.18 [XQuery1.0XPath2.0/2] Section 7.5.4 fn:substring-before

The **fn:substring-before** function is not supported by XQuery in SQL Server.

2.1.6.3.19 [XQuery1.0XPath2.0/2] Section 7.5.5 fn:substring-after

The **fn:substring-after** function is not supported by XQuery in SQL Server.

2.1.6.3.20 [XQuery1.0XPath2.0/2] Section 7.6.2 fn:matches

The **fn:matches** function is not supported by XQuery in SQL Server.

2.1.6.3.21 [XQuery1.0XPath2.0/2] Section 7.6.3 fn:replace

The **fn:replace** function is not supported by XQuery in SQL Server.

2.1.6.3.22 [XQuery1.0XPath2.0/2] Section 7.6.4 fn:tokenize

The **fn:tokenize** function is not supported by XQuery in SQL Server.

2.1.6.4 anyURI Functions

2.1.6.4.1 [XQuery1.0XPath2.0/2] Section 8.1 fn:resolve-uri

The **fn:resolve-uri** function is not supported by XQuery in SQL Server.

2.1.6.5 Durations, Dates, and Times Functions

2.1.6.5.1 [XQuery1.0XPath2.0/2] Section 10.5.1 fn:years-from-duration

The **fn:years-from-duration** function is not supported by XQuery in SQL Server.

2.1.6.5.2 [XQuery1.0XPath2.0/2] Section 10.5.2 fn:months-from-duration

The **fn:months-from-duration** function is not supported by XQuery in SQL Server.

2.1.6.5.3 [XQuery1.0XPath2.0/2] Section 10.5.3 fn:days-from-duration

The **fn:days-from-duration** function is not supported by XQuery in SQL Server.

2.1.6.5.4 [XQuery1.0XPath2.0/2] Section 10.5.4 fn:hours-from-duration

The **fn:hours-from-duration** function is not supported by XQuery in SQL Server.

2.1.6.5.5 [XQuery1.0XPath2.0/2] Section 10.5.5 fn:minutes-from-duration

The **fn:minutes-from-duration** function is not supported by XQuery in SQL Server.

2.1.6.5.6 [XQuery1.0XPath2.0/2] Section 10.5.6 fn:seconds-from-duration

The **fn:seconds-from-duration** function is not supported by XQuery in SQL Server.

2.1.6.5.7 [XQuery1.0XPath2.0/2] Section 10.5.7 fn:year-from-dateTime

The **fn:year-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.8 [XQuery1.0XPath2.0/2] Section 10.5.8 fn:month-from-dateTime

The **fn:month-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.9 [XQuery1.0XPath2.0/2] Section 10.5.9 fn:day-from-dateTime

The **fn:day-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.10 [XQuery1.0XPath2.0/2] Section 10.5.10 fn:hours-from-dateTime

The **fn:hours-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.11 [XQuery1.0XPath2.0/2] Section 10.5.11 fn:minutes-from-dateTime

The **fn:minutes-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.12 [XQuery1.0XPath2.0/2] Section 10.5.12 fn:seconds-from-dateTime

The **fn:seconds-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.13 [XQuery1.0XPath2.0/2] Section 10.5.13 fn:timezone-from-dateTime

The **fn:timezone-from-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.5.14 [XQuery1.0XPath2.0/2] Section 10.5.14 fn:year-from-date

The **fn:year-from-date** function is not supported by XQuery in SQL Server.

2.1.6.5.15 [XQuery1.0XPath2.0/2] Section 10.5.15 fn:month-from-date

The **fn:month-from-date** function is not supported by XQuery in SQL Server.

2.1.6.5.16 [XQuery1.0XPath2.0/2] Section 10.5.16 fn:day-from-date

The **fn:day-from-date** function is not supported by XQuery in SQL Server.

2.1.6.5.17 [XQuery1.0XPath2.0/2] Section 10.5.17 fn:timezone-from-date

The **fn:timezone-from-date** function is not supported by XQuery in SQL Server.

2.1.6.5.18 [XQuery1.0XPath2.0/2] Section 10.5.18 fn:hours-from-time

The **fn:hours-from-time** function is not supported by XQuery in SQL Server.

2.1.6.5.19 [XQuery1.0XPath2.0/2] Section 10.5.19 fn:minutes-from-time

The **fn:minutes-from-time** function is not supported by XQuery in SQL Server.

2.1.6.5.20 [XQuery1.0XPath2.0/2] Section 10.5.20 fn:seconds-from-time

The **fn:seconds-from-time** function is not supported by XQuery in SQL Server.

2.1.6.5.21 [XQuery1.0XPath2.0/2] Section 10.5.21 fn:timezone-from-time

The **fn:timezone-from-time** function is not supported by XQuery in SQL Server.

2.1.6.5.22 [XQuery1.0XPath2.0/2] Section 10.7.1 fn:adjust-dateTime-to-timezone

The **fn:resolve-uri** function is not supported by XQuery in SQL Server.

2.1.6.5.23 [XQuery1.0XPath2.0/2] Section 10.7.2 fn:adjust-date-to-timezone

The **fn:adjust-date-to-timezone** function is not supported by XQuery in SQL Server.

2.1.6.5.24 [XQuery1.0XPath2.0/2] Section 10.7.3 fn:adjust-time-to-timezone

The **fn:adjust-time-to-timezone** function is not supported by XQuery in SQL Server.

2.1.6.6 QName Functions

2.1.6.6.1 [XQuery1.0XPath2.0/2] Section 11.1.1 fn:resolve-QName

The **fn:resolve-QName** function is not supported by XQuery in SQL Server.

2.1.6.6.2 [XQuery1.0XPath2.0/2] Section 11.1.2 fn:QName

The **fn:QName** function is not supported by XQuery in SQL Server.

2.1.6.6.3 [XQuery1.0XPath2.0/2] Section 11.2.2 fn:prefix-from-QName

The **fn:prefix-from-QName** function is not supported by XQuery in SQL Server.

2.1.6.6.4 [XQuery1.0XPath2.0/2] Section 11.2.3 fn:local-name-from-QName

The **fn:local-name-from-QName** function is supported by XQuery in SQL Server with a variation. The form **fn:local-name()** (with no arguments) can be used only within a context-dependent predicate.

2.1.6.6.5 [XQuery1.0XPath2.0/2] Section 11.2.5 fn:namespace-uri-for-prefix

The **fn:namespace-uri-from-QName** function is not supported by XQuery in SQL Server.

2.1.6.6.6 [XQuery1.0XPath2.0/2] Section 11.2.6 fn:in-scope-prefixes

The **fn:in-scope-prefixes** function is not supported by XQuery in SQL Server.

2.1.6.7 base64Binary and hexBinary Functions

The standard does not specify any functions for **base64Binary** and **hexBinary**.

2.1.6.8 Notation Functions

The standard does not specify any functions for **Notation**.

2.1.6.9 Nodes Functions

2.1.6.9.1 [XQuery1.0XPath2.0/2] Section 14.1 fn:name

The **fn:name** function is not supported by XQuery in SQL Server.

2.1.6.9.2 [XQuery1.0XPath2.0/2] Section 14.3 fn:namespace-uri

The **fn:namespace-uri** function is supported by XQuery in SQL Server with a variation. XQuery in SQL Server returns a value of type **xs:string**, while [XQuery1.0XPath2.0/2] specifies that a value of type **xs:anyURI** be returned. In XQuery in SQL Server, the form **fn:namespace-uri()** (with no arguments) can be used only within a context-dependent predicate.

2.1.6.9.3 [XQuery1.0XPath2.0/2] Section 14.4 fn:number

The **fn:number** function is supported by XQuery in SQL Server with a variation. XQuery in SQL Server supports the argument *\$arg* as type node, while [XQuery1.0XPath2.0/2] specifies the argument *\$arg* to be of type **xs:anyAtomicType**. The form **fn:number()** (with no arguments) can be used only within a context-dependent predicate.

2.1.6.9.4 [XQuery1.0XPath2.0/2] Section 14.5 fn:lang

The **fn:lang** function is not supported by XQuery in SQL Server.

2.1.6.9.5 [XQuery1.0XPath2.0/2] Section 14.9 fn:root

The **fn:root** function is not supported by XQuery in SQL Server.

2.1.6.10 Sequences Functions

2.1.6.10.1 [XQuery1.0XPath2.0/2] Section 15.1.1 fn:boolean

The **fn:boolean** function is not supported by XQuery in SQL Server.

2.1.6.10.2 [XQuery1.0XPath2.0/2] Section 15.1.3 fn:index-of

The **fn:index-of** function is not supported by XQuery in SQL Server.

2.1.6.10.3 [XQuery1.0XPath2.0/2] Section 15.1.5 fn:exists

The **fn:exists** function is not supported by XQuery in SQL Server.

2.1.6.10.4 [XQuery1.0XPath2.0/2] Section 15.1.6 fn:distinct-values

The **fn:distinct-values** function is supported by XQuery in SQL Server with a variation. The *\$collation* optional argument is not supported.

XQuery in SQL Server requires that all of the arguments to the function be of the same type, and that the types either be one of the following types or be descended from one of them:

- One of the numeric base types
- One of the date/time base types
- The **xs:string** type
- The **xs:boolean** type
- The **xdt:untypedAtomic** type

The **xdt:untypedAtomic** type is cast to **xs:string**. The **fn:distinct-values** function is not supported for **xs:duration**.

2.1.6.10.5 [XQuery1.0XPath2.0/2] Section 15.1.7 fn:insert-before

The **fn:insert-before** function is not supported by XQuery in SQL Server.

2.1.6.10.6 [XQuery1.0XPath2.0/2] Section 15.1.8 fn:remove

The **fn:remove** function is not supported by XQuery in SQL Server.

2.1.6.10.7 [XQuery1.0XPath2.0/2] Section 15.1.9 fn:reverse

The **fn:reverse** function is not supported by XQuery in SQL Server.

2.1.6.10.8 [XQuery1.0XPath2.0/2] Section 15.1.10 fn:subsequence

The **fn:subsequence** function is not supported by XQuery in SQL Server.

2.1.6.10.9 [XQuery1.0XPath2.0/2] Section 15.1.11 fn:unordered

The **fn:unordered** function is not supported by XQuery in SQL Server.

2.1.6.10.10 [XQuery1.0XPath2.0/2] Section 15.2.1 fn:zero-or-one

The **fn:zero-or-one** function is not supported by XQuery in SQL Server.

2.1.6.10.11 [XQuery1.0XPath2.0/2] Section 15.2.2 fn:one-or-more

The **fn:one-or-more** function is not supported by XQuery in SQL Server.

2.1.6.10.12 [XQuery1.0XPath2.0/2] Section 15.2.3 fn:exactly-one

The **fn:exactly-one** function is not supported by XQuery in SQL Server.

2.1.6.10.13 [XQuery1.0XPath2.0/2] Section 15.3.1 fn:deep-equal

The **fn:deep-equal** function is not supported by XQuery in SQL Server.

2.1.6.10.14 [XQuery1.0XPath2.0/2] Section 15.4.2 fn:avg

The **fn:avg** function is supported by XQuery in SQL Server, with a variation. The W3C specification [XQuery1.0XPath2.0/2] specifies **xs:anyAtomicType** for the argument *\$arg*. XQuery in SQL Server requires ~~that~~ the values that are passed as *\$arg* mustto be a subtype of exactly one of the three built-in numeric base types or the **xdt:untypedAtomic** type. The values cannot be a mixture of numeric base types and **xdt:untypedAtomic**.

2.1.6.10.15 [XQuery1.0XPath2.0/2] Section 15.4.3 fn:max

The **fn:max** function is supported by XQuery in SQL Server, with a variation. [XQuery1.0XPath2.0/2] specifies **xs:anyAtomicType** for the argument *\$arg*.

[XQuery1.0XPath2.0/2] specifies an optional second argument, *\$collation*. XQuery in SQL Server does not support the optional argument *\$collation*.

XQuery in SQL Server requires ~~that~~ all the values that are passed as *\$arg* mustto be of exactly one type. Allowed types are a subtype of exactly one of the three built-in numeric base types, the date/time base types, **xs:string**, **xs:boolean**, or **xdt:untypedAtomic**.

2.1.6.10.16 [XQuery1.0XPath2.0/2] Section 15.4.4 fn:min

The **fn:min** function is supported by XQuery in SQL Server, with a variation. [XQuery1.0XPath2.0/2] specifies **xs:anyAtomicType** for the argument *\$arg*. [XQuery1.0XPath2.0/2] specifies an optional second argument, *\$collation*. XQuery in SQL Server does not support the optional argument *\$collation*.

XQuery in SQL Server requires ~~that~~ all the values that are passed as *\$arg* mustto be of exactly one type. Allowed types are a subtype of exactly one of the three built-in numeric base types, the date/time base types, **xs:string**, **xs:boolean**, or **xdt:untypedAtomic**.

2.1.6.10.17 [XQuery1.0XPath2.0/2] Section 15.4.5 fn:sum

The **fn:sum** function is supported by XQuery in SQL Server, with a variation. [XQuery1.0XPath2.0/2] specifies an optional second argument, *\$zero*. XQuery in SQL Server does not support the optional argument *\$zero*.

[XQuery1.0XPath2.0/2] specifies **xs:anyAtomicType** for the argument *\$arg*. XQuery in SQL Server requires ~~that~~ the values that are passed as *\$arg* mustto be a subtype of exactly one of the three built-in numeric base types or **xdt:untypedAtomic**. The values cannot be a mixture of types.

2.1.6.10.18 [XQuery1.0XPath2.0/2] Section 15.5.2 fn:id

The **fn:id** function is supported by XQuery in SQL Server, with a variation. The W3C specification [XQuery1.0XPath2.0/2] specifies an optional second argument, *\$node*. XQuery in SQL Server does not support the optional argument *\$node*.

[XQuery1.0XPath2.0/2] specifies **xs:string** for the argument *\$arg*. XQuery in SQL Server specifies that the argument *\$arg* is of type **xs:IDREF**.

2.1.6.10.19 [XQuery1.0XPath2.0/2] Section 15.5.3 fn:idref

The **fn:idref** function is not supported by XQuery in SQL Server.

2.1.6.10.20 [XQuery1.0XPath2.0/2] Section 15.5.4 fn:doc

The **fn:doc** function is not supported by XQuery in SQL Server.

2.1.6.10.21 [XQuery1.0XPath2.0/2] Section 15.5.5 fn:doc-available

The **fn:doc-available** function is not supported by XQuery in SQL Server.

2.1.6.10.22 [XQuery1.0XPath2.0/2] Section 15.5.6 fn:collection

The **fn:collection** function is not supported by XQuery in SQL Server.

2.1.6.10.23 [XQuery1.0XPath2.0/2] Section 15.5.7 fn:element-with-id

The **fn:element-with-id** function is not supported by XQuery in SQL Server.

2.1.6.11 Context

2.1.6.11.1 [XQuery1.0XPath2.0/2] Section 16.1 fn:position

The **fn:position** function is supported by XQuery in SQL Server with a variation. The form **fn:position()** (with no arguments) can be used only within a context-dependent predicate.

2.1.6.11.2 [XQuery1.0XPath2.0/2] Section 16.2 fn:last

The **fn:last** function is supported by XQuery in SQL Server with a variation. The form **fn:last()** (with no arguments) can be used only within a context-dependent predicate.

2.1.6.11.3 [XQuery1.0XPath2.0/2] Section 16.3 fn:current-dateTime

The **fn:current-dateTime** function is not supported by XQuery in SQL Server.

2.1.6.11.4 [XQuery1.0XPath2.0/2] Section 16.4 fn:current-date

The **fn:current-date** function is not supported by XQuery in SQL Server.

2.1.6.11.5 [XQuery1.0XPath2.0/2] Section 16.5 fn:current-time

The **fn:current-time** function is not supported by XQuery in SQL Server.

2.1.6.11.6 [XQuery1.0XPath2.0/2] Section 16.6 fn:implicit-timezone

The **fn:implicit-timezone** function is not supported by XQuery in SQL Server.

2.1.6.11.7 [XQuery1.0XPath2.0/2] Section 16.7 fn:default-collation

The **fn:default-collation** function is not supported by XQuery in SQL Server.

2.1.6.11.8 [XQuery1.0XPath2.0/2] Section 16.8 fn:static-base-uri

The **fn:static-base-uri** function is not supported by XQuery in SQL Server.

2.2 Clarifications

The following subsections identify clarifications relative to XQuery in SQL Server.

Unless otherwise stated, the specified products conform to all SHOULD and RECOMMENDED behavior in XQuery in SQL Server.

2.2.1 [XDM/2] Section 3.3.1.3, Relationship Between Typed-Value and String-Value

C00001:

The specification allows values to be stored as a typed value or as a string representation of a typed value. XQuery in SQL Server stores values as a typed value.

2.2.2 [XDM/2] Section 3.3.1.4, Pattern Facets

C00002:

The specification states that pattern facets, by their nature, ~~may not~~cannot be round-trippable. XQuery in SQL Server stores values as a typed representation, so pattern facets that are not encapsulated in the storage of a typed value are not round-trippable.

2.2.3 [XDM/2] Section 6.2.4, Element Nodes, Construction from a PSVI

C00003:

The specification states that the processor ~~MAY~~can use a sequence of nodes that are processing instruction nodes or comment nodes, in the children collection. XQuery in SQL Server supports processing instruction nodes or comment nodes in the collection of children nodes.

If an element has simple typed content and contains either processing instruction or comment nodes or both, XQuery in SQL Server moves all the processing instruction children nodes and all the comment children nodes to the front of the collection of children nodes, preserving order, and combines all the text children nodes into one typed text node value that follows the other children nodes.

2.2.4 [XQuery1.0/2] Section 5.2, Optional Features

2.2.4.1 [XQuery1.0/2] Section 5.2.1, Schema Import Feature

C00004:

XQuery in SQL Server does not support the schema import feature. However, XQuery in SQL Server implicitly supports schema import by using the XML schema collection that is associated with an XML data type.

2.2.4.2 [XQuery1.0/2] Section 5.2.2, Schema Validation Feature

C00005:

XQuery in SQL Server supports the schema validation feature.

2.2.4.3 [XQuery1.0/2] Section 5.2.3, Static Typing Feature

C00006:

XQuery in SQL Server supports the static typing feature.

2.2.4.4 [XQuery1.0/2] Section 5.2.4, Full Axis Feature

C00007:

XQuery in SQL Server does not support the Full Axis feature

2.2.4.5 [XQuery1.0/2] Section 5.2.5, Module Feature

C00008:

XQuery in SQL Server does not support the Module feature.

2.2.4.6 [XQuery1.0/2] Section 5.2.6, Serialization Feature

C00009:

XQuery in SQL Server does not support the Serialization feature.

2.2.5 sql:column Function

E00001:

XQuery in SQL Server extends the [XQuery1.0XPath2.0/2] specification with the **sql:column** function. See [MSDN-sqlcolumnXQuery].

2.2.6 sql:variable Function

E00002:

XQuery in SQL Server extends the [XQuery1.0XPath2.0/2] specification with the **sql:variable** function. See [MSDN-sqlvariableXQuery].

2.3 Error Handling

None.

2.4 Security

None.

3 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

4 Index

C

Change tracking 57

D

Dynamic Evaluation Phase 16

E

Element Nodes - Construction from a PSVI 55

F

Full Axis Feature 55

G

Glossary 10

I

Informative references 11

Introduction 10

M

Module Feature 56

N

Normative references 10

numeric functions 46

P

Pattern Facets 55

R

References

 informative 11

 normative 10

Relationship Between Typed-Value and String-Value 55

S

Schema Import Feature 55

Schema Validation Feature 55

Serialization Feature 56

Static Analysis Phase 16

Static Typing Feature 55

T

Tracking changes 57